

# **Dell Express Flash P5500 and P5600**

## Technical Specifications and Information

## Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

# Technical Specifications and Information

Use these specifications and model-specific information to ensure optimal functioning of your Dell Express Flash P5500 and P5600 drives.


**Table 1. P5500 and P5600 technical specifications**

Features	P5500	P5600
Media type	96 layer 3D NAND	96 layer 3D NAND
Capacities	1.92 TB 3.84 TB 7.68 TB	1.6 TB 3.2 TB 6.4 TB
User-addressable 512-byte sectors	1.92 TB: 3,750,748,848 3.84 TB: 7,501,476,528 7.68 TB: 15,002,931,888	1.6 TB: 3,125,627,568 3.2 TB: 6,251,233,968 6.4 TB: 12,502,446,768
Host bus interface	PCIe Gen 4.0 x 4	PCIe Gen 4.0 x 4
Device protocol	NVM Express 1.3c	NVM Express 1.3c
TCG support	TCG Storage Security Subsystem Class: Opal Specification Version 2.01 Revision 1.00.	TCG Storage Security Subsystem Class: Opal Specification Version 2.01 Revision 1.00.
Instant Secure Erase (ISE) support	National Institute for Standards and Technology (NIST) Special Publication 800-88 Revision 1, Guidelines for Media Sanitization.	National Institute for Standards and Technology (NIST) Special Publication 800-88 Revision 1, Guidelines for Media Sanitization.
Bootable device	Yes, UEFI mode only	Yes, UEFI mode only
Hot-swap support	Yes Minimum version of OS to support hot-swap: <ul style="list-style-type: none"> <li>Windows 2019 and later</li> <li>RHEL 8.2</li> <li>SLES 15 SP2</li> <li>Ubuntu 20.4</li> <li>ESX 7.0 (Supported with exceptions, see <a href="http://www.dell.com/virtualizationsolutions">www.dell.com/virtualizationsolutions</a> for more information.)</li> </ul>	Yes Minimum versions of OS to support hot-swap: <ul style="list-style-type: none"> <li>Windows 2019 and later</li> <li>RHEL 8.2</li> <li>SLES 15 SP2</li> <li>Ubuntu 20.4</li> <li>ESX 7.0 (Supported with exceptions, see <a href="http://www.dell.com/virtualizationsolutions">www.dell.com/virtualizationsolutions</a> for more information.)</li> </ul>
Endurance rating (TBW) (Warranty period - 5 years)	1.92 TB: 1 DWPD, 3,540 TB 3.84 TB: 1 DWPD, 7,008 TB 7.68 TB: 1 DWPD, 14,016 TB	1.6 TB: 3 DWPD, 8,760 TB 3.2 TB: 3 DWPD, 17,520 TB 6.4 TB: 3 DWPD, 35,040 TB
Data retention at maximum rated endurance as per JEDEC requirements	3 months at 40°C	3 months at 40°C

**Table 1. P5500 and P5600 technical specifications (continued)**

<b>Features</b>	<b>P5500</b>	<b>P5600</b>
Power	12 V, 3.3 V aux, supply rail 5.0 W idle, typical 25 W active, max	12 V, 3.3 V aux, supply rail 5.0 W idle, typical 25 W active, max
Operating temperature	0 °C–70°C with specified air flow	0 °C–70°C with specified air flow
Physical dimensions (width x length x thickness)	100.45 mm x 69.85 mm x 15.00 mm	100.45 mm x 69.85 mm x 15.00 mm
Weight	146g +/- 15g	146g +/- 15g
Shock	1,000 G/0.5 millisecond	1,000 G/0.5 millisecond
Vibration	2.17 Grms, 5 Hz ~ 700 Hz—Operating 3.13 Grms, 5 Hz ~ 800 Hz—Non-operating	2.17 Grms, 5 Hz ~ 800 Hz—Operating 3.13 Grms, 5 Hz ~ 800 Hz—Non-operating
IOPS 4K random reads (16 queue depth; 16 workers)	1.92 TB: up to 420,000 IOPS 3.84 TB: up to 770,000 IOPS 7.68 TB: up to 990,000 IOPS	1.6 TB : up to 420,000 IOPS 3.2 TB : up to 780,000 IOPS 6.4 TB : up to 990,000 IOPS
IOPS 4K random writes (16 queue depth; 16 workers)	1.92 TB: up to 65,000 IOPS 3.84 TB: up to 130,000 IOPS 7.68 TB: up to 160,000 IOPS	1.6 TB: up to 130,000 IOPS 3.2 TB: up to 260,000 IOPS 6.4 TB: up to 300,000 IOPS
Latency 4K random read (1 queue depth)	1.92 TB: 10 µs to 78 µs 3.84 TB: 10 µs to 78 µs 7.68 TB: 10 µs to 78 µs	1.6 TB: 10 µs to 78 µs 3.2 TB: 9 µs to 78 µs 6.4 TB: 9 µs to 78 µs
Latency 4K random write (1 queue depth)	1.92 TB: 12 µs to 22 µs 3.84 TB: 12 µs to 17 µs 7.68 TB: 12 µs to 15 µs	1.6 TB : 13 µs to 16 µs 3.2 TB : 12 µs to 14 µs 6.4 TB : 12 µs to 14 µs
IOPS 8K random reads (16 queue depth; 16 worker)	1.92 TB: 220,000 IOPS 3.84 TB: 430,000 IOPS 7.68 TB: 590,000 IOPS	1.6 TB: 230,000 IOPS 3.2 TB: 430,000 IOPS 6.4 TB: 600,000 IOPS
IOPS 8K random writes (16 queue depth; 16 worker)	1.92 TB: up to 35,000 IOPS 3.84 TB: up to 65,000 IOPS 7.68 TB: up to 85,000 IOPS	1.6 TB: up to 65,000 IOPS 3.2 TB: up to 135,000 IOPS 6.4 TB: up to 160,000 IOPS
Sequential read (128 queue depth; 1 worker)	1.92 TB: 3.8 GB/s 3.84 TB: 6.7 GB/s 7.68 TB: 6.7 GB/s	1.6 TB: 3.8 GB/s 3.2 TB: 6.7 GB/s 6.4 TB: 6.7 GB/s
Sequential write (128 queue depth; 1 worker)	1.92 TB: 1.9 GB/s 3.84 TB: 3.7 GB/s 7.68 TB: 4.6 GB/s	1.6 TB: 1.8 GB/s 3.2 TB: 3.7 GB/s 6.4 TB: 4.6 GB/s

# Minimum supported operating systems

 **NOTE:** Supported on all operating systems using the included native drivers.

- Microsoft
  - Windows Server 2019
  - Windows Server 2016
- Linux
  - Red Hat Enterprise Linux 8.0
  - Red Hat Enterprise Linux 7.5
  - SUSE Linux Enterprise Server 15
- Ubuntu
  - Ubuntu 20.04
  - Ubuntu 18.04
- VMware
  - ESXi 7.0
  - ESXi 6.7