
Dell Inc. One Dell Way Round Rock, TX 78682 Telephone: 512.338.4400 Telefax: 512.728.3653



Date: December 18th, 2017

Subject: Statement of Volatility – Dell M318WL Projector

To whom it may concern:

The purpose of this document is to certify that the Dell M318WL projector will not save, retain, or reproduce a signal to any internal or external component after power has been removed and reapplied to the unit.

The Dell M318WL projector contains both volatile and non-volatile (NV) memory ICs. Volatile memory(s) lose their data immediately upon removal of power. Non-volatile memory ICs continue to retain their data even after the power has been removed. However, no input video data is written into these memory ICs during operation.

The list below contains volatile and non-volatile memory ICs used in the Dell M318WL projector.

System EEPROM	HT24LC32
Size	32K bit
Type [e.g. Flash PROM, EEPROM]	EEPROM
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	OSD setting: Yes
Purpose	Storage of system setting (OSD)
How is data input to this memory?	Control the OSD menu and change OSD setting(ex. Brightness, contrast, color setting) and the setting will be stored into system EEPROM
How is this memory write protected?	Software write protected

HDMI EDID EEPROM	GT24C02A-2TFLI-TR
Size	2Kbit
Type [e.g. Flash PROM, EEPROM]	EEPROM
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of HDMI EDID
How is data input to this memory?	Writing EDID requires a customized EDID tool.
How is this memory write protected?	Hardware and software write protected

Multimedia NAND Flash	MT29F64G08CBABAW
Size	64G bit (8G x 8)
Type [e.g. Flash PROM, EEPROM]	NAND Flash memory
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of AM8250 firmware     Storage of user's data (Ex: Document, photo, music, video)
How is data input to this memory?	<ol> <li>Writing AM8250 firmware requires a customized programming tool.</li> <li>Copy files via USB A to A cable.</li> </ol>
How is this memory write protected?	Hardware and software write protected (AM8250 firmware)     Internal memory is free to access and delete.

System NOR Flash	MX29LV640EBTI-70G
Size	64M bit (8M x 8)
Type [e.g. Flash PROM, EEPROM]	NOR Flash memory
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of DDP6401 firmware
How is data input to this memory?	Writing DDP6401 firmware requires a customized programming tool.

How is this memory write protected?	Hardware and software write protected
-------------------------------------	---------------------------------------

MCU on chip Flash	PIC24FJ32GA002
Size	32K Byte Flash
Type [e.g. Flash PROM, EEPROM]	MCU (on chip flash memory)
Volatility	Non-volatile
Can user programs or operating system write data to it during normal operation?	No
Purpose	Storage of MCU firmware
How is data input to this memory?	Writing MCU firmware via UART port at download mode.
How is this memory write protected?	Software write protected.

Please direct any questions to your Dell Marketing contact.

Sincerely,

Dell Marketing