

Statement of Volatility -Dell Latitude E5430/E5530

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

The Dell Latitude E5430/E5530 contains both volatile and non-volatile (NV) components. Volatile components lose their data immediately after power is removed from the component. Non-volatile (NV) components continue to retain their data even after power is removed from the component. The following NV components are present on the Dell Latitude E5430/E5530 system board.

Table 1. List of Non-Volatile Components on System Board

| Description | Reference Designator | Volatility Description | User Accessible for external data | Remedial Action (Action necessary to prevent loss of data) |
|---|---|---|---|--|
| Embedded Flash in embedded controller MEC5035 | U3 | 192 KB of embedded Flash memory for keyboard controller BIOS code, asset tag, and BIOS passwords. | No | N/A |
| Panel EEDID EEPROM | Part of panel assembly | Non-volatile memory, 512 bytes. | No | Part of panel assembly |
| System BIOS | U18 | Non-volatile memory, 32 Mbit (4 MB), System BIOS and Video BIOS for basic boot operation, PSA (on board diags), PXE diags. | No | N/A |
| Video BIOS | On GFx cards (G92 or G94) | Non-volatile memory, 512 kbit (64 KB), Graphics system BIOS. | No | N/A |
| System Memory – DDR3 memory | Four SODIMM connectors: JDIM1,2,3,4 | Volatile memory in OFF state Two to four modules must be populated. System memory size will depend on SODIMM modules and must be between 2 GB and 16 GB. | Yes | Power off system |
| System memory SPD EEPROM | On System memory SODIMM(s) 2-4 present | Non-volatile memory 512 Bytes. Stores memory, manufacturer data, and timing information for correct operation of system memory. | No | N/A |

| Description | Reference Designator | Volatility Description | User Accessible for external data | Remedial Action (Action necessary to prevent loss of data) |
|---|--|---|---|--|
| RTC CMOS - BBRAM (battery backed up) | U3 | Non-volatile memory, 64 Bytes. Stores CMOS information. | No | N/A |
| Video memory – frame buffer | On GFx cards (G92 or G94): U2A, U2B, U3A, U3B, U4A, U4B, U5A, U5B, U6A, U6B, U7A, U7B, U8A, U8B, U9A, U9B | Volatile memory in off state. 1 GB GDDR3 for G92 discrete graphics systems. 256 MB GDDR3 for G94 discrete graphics systems. | No | N/A |
| LOM Serial Flash Memory | U18 | Non-volatile memory, 8 Mbit (2 MB) MAC address, LED mode, WOL settings, PXE settings. | No | N/A |
| Hard drive(s) | User replaceable - one or two. | Non-volatile magnetic media, various sizes in GB. May also be SSD (solid state flash drive). | Yes | Low-level format |
| CD- ROM/RW/ DVD/ DVD+RW/ Diskette Drives | User replaceable | Non-volatile optical media. | Yes | Low-level format/erase |

CAUTION: All other components on the system board lose data if power is removed from the system. Primary power loss (unplugging the power cord and removing the battery) destroys all user data on the memory (DDR3, 1067 MHz). Secondary power loss (removing the on-board coin-cell battery) destroys system data on the system configuration and time-of-day information.

© 2012 Dell Inc.

Trademarks used in this text: Dell™, the DELL logo, Dell Precision™, OptiPlex™, Latitude™, PowerEdge™, PowerVault™, PowerConnect™, OpenManage™, EqualLogic™, KACE™, FlexAddress™ and Vostro™ are trademarks of Dell Inc. Intel®, Pentium®, Xeon®, Core™ and Celeron® are registered trademarks of Intel Corporation in the U.S. and other countries. AMD® is a registered trademark and AMD Opteron™, AMD Phenom™, and AMD Sempron™ are trademarks of Advanced Micro Devices, Inc. Microsoft®, Windows®, Windows Server®, MS-DOS® and Windows Vista® are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Red Hat Enterprise Linux® and Enterprise Linux® are registered trademarks of Red Hat, Inc. in the United States and/or other countries. Novell® is a registered trademark and SUSE ™ is a trademark of Novell Inc. in the United States and other countries. Oracle® is a registered trademark of Oracle Corporation and/or its affiliates. Citrix®, Xen®, XenServer® and XenMotion® are either registered trademarks or trademarks of Citrix Systems, Inc. in the United States and/or other countries. VMware®, Virtual SMP®, vMotion®, vCenter®, and vSphere® are registered trademarks or trademarks of VMWare, Inc. in the United States or other countries.