

Dell EMC S3048-ON System Release Notes, OS Version 9.14(1.10)

This document contains information on open and resolved caveats, and operational information specific to the Dell EMC Networking OS software and the S3048-ON platform.

Current Release Version: 9.14(1.10)

Release Date: 2021-09-30

Previous Release Version: 9.14(1.9P4)

Topics:

- [Document Revision History](#)
- [Supported Hardware](#)
- [Supported Software](#)
- [New Dell EMC Networking OS Version 9.14\(1.10\) Features](#)
- [Restrictions](#)
- [Changes to Default Behavior and CLI Syntax](#)
- [Documentation Corrections](#)
- [Deferred Issues](#)
- [Fixed Issues](#)
- [Known Issues](#)
- [Upgrading ONIE on the S3048-ON](#)
- [Installing Dell EMC Networking OS on the S3048-ON using ONIE](#)
- [Upgrading the S3048-ON Dell EMC Networking OS Image using the Dell EMC Networking OS CLI](#)
- [Upgrading the CPLD](#)
- [Upgrade the BIOS from Dell EMC Networking OS](#)
- [Uninstalling Dell EMC Networking OS on the S3048-ON](#)
- [Installing a Third Party Operating System](#)
- [Support Resources](#)

For more information on hardware and software features, commands, and capabilities, refer to the Dell EMC Networking support website at: <https://www.dell.com/support>

Document Revision History

Table 1. Revision History

Date	Description
2021-09	Initial release.

Supported Hardware

The following hardware is supported with this platform:

Hardware
S3048-ON chassis

Hardware
Forty-eight 10/100/1000Base-T RJ-45 Ports
Four SFP+ optical ports (10 Gbps)
Management Port
USB 2.0 Port
Serial Console Port
Two AC PSUs
Three fan subsystems

NOTE: If all the three fan trays are found to be empty or faulty, the system shuts down after one minute.

Supported Software

The following software is supported with this platform:

Software	Minimum Release Requirement
Dell EMC Networking OS	9.14(1.10)
ONIE	3.24.1.0-4

NOTE: For information on non-Dell OS versions, refer the *Release Notes for the Hardware Platform S3048-ON*.

New Dell EMC Networking OS Version 9.14(1.10) Features

The following features have been added to the S3048-ON with Dell EMC Networking OS version 9.14(1.10):

None.

Restrictions

- If you downgrade the Dell EMC Networking OS from 9.14(1.10) to 9.11(0.0) or any older version, the system displays the following error message even though there is no functional impact:

```
CDB boot error:      C.cdb file format
```

Before downgrading, save the current configuration and then remove the CDB files (`confd_cdb.tar.gz.version` and `confd_cdb.tar.gz`). To remove the files, use the following steps:

```
DellEMC#write memory
DellEMC#delete flash://confd_cdb.tar.gz.version
DellEMC#delete flash://confd_cdb.tar.gz
DellEMC#reload
```

- While deploying the system in the normal-reload mode in BMP configuration, use the `ip ssh server enable` command at the beginning of the startup configuration if the write memory command is used at the end of the configuration.
- REST API does not support AAA authentication.

- The following features are not available in the Dell EMC Networking OS from version 9.7(0.0):
 - PIM ECMP
 - Static IGMP join (`ip igmp static-group`)
 - IGMP querier timeout configuration (`ip igmp querier-timeout`)
 - IGMP group join limit (`ip igmp group join-limit`)
- Half-Duplex mode is not supported.
- When FRRP is enabled in a VLT domain, no flavor of Spanning tree should concurrently be enabled on the nodes of that specific VLT domain. In essence FRRP and xSTP should not co-exist in a VLT environment.

Changes to Default Behavior and CLI Syntax

Following default behavior and CLI syntax changes occurred during the Dell EMC Networking OS release:

- To enhance security, the default RSA key size has been changed to 2048 bits from 1024 bits from 9.14.1.10 onwards.

Documentation Corrections

This section describes the errors identified in the current release of the Dell EMC Networking OS.

None.

Deferred Issues

Issues that appear in this section were reported in Dell EMC Networking OS version 9.14(1.0) as open, but have since been deferred. Deferred issues are those that are found to be invalid, not reproducible, or not scheduled for resolution.

Deferred issues are reported using the following definitions.

Category	Description
PR#	Problem Report number that identifies the issue.
Severity	<p>S1 — Crash: A software crash occurs in the kernel or a running process that requires a restart of AFM, the router, switch, or process.</p> <p>S2 — Critical: An issue that renders the system or a major feature unusable, which can have a pervasive impact on the system or network, and for which there is no work-around acceptable to the customer.</p> <p>S3 — Major: An issue that affects the functionality of a major feature or negatively effects the network for which there exists a work-around that is acceptable to the customer.</p> <p>S4 — Minor: A cosmetic issue or an issue in a minor feature with little or no network impact for which there might be a work-around.</p>
Synopsis	Synopsis is the title or short description of the issue.
Release Notes	Release Notes description contains more detailed information about the issue.
Work around	<p>Work around describes a mechanism for circumventing, avoiding, or recovering from the issue. It might not be a permanent solution.</p> <p>Issues listed in the “Fixed Issues” section should not be present, and the work-around is unnecessary, as the version of code for which this release note is documented has resolved the issue.</p>

Deferred S3048–ON 9.14(1.0) Software Issues

Issues that appear in this section were reported in Dell EMC Networking OS version 9.14(1.0) as open, but have since been deferred. Deferred caveats are those that are found to be invalid, not reproducible, or not scheduled for resolution.

The following issues have been deferred in the Dell EMC Networking OS version 9.14(1.0):


None.

Fixed Issues

Fixed issues are reported using the following definitions.

Category	Description
PR#	Problem Report number that identifies the issue.
Severity	S1 — Crash: A software crash occurs in the kernel or a running process that requires a restart of AFM, the router, switch, or process. S2 — Critical: An issue that renders the system or a major feature unusable, which can have a pervasive impact on the system or network, and for which there is no work-around acceptable to the customer. S3 — Major: An issue that affects the functionality of a major feature or negatively effects the network for which there exists a work-around that is acceptable to the customer. S4 — Minor: A cosmetic issue or an issue in a minor feature with little or no network impact for which there might be a work-around.
Synopsis	Synopsis is the title or short description of the issue.
Release Notes	Release Notes description contains more detailed information about the issue.
Work around	Work around describes a mechanism for circumventing, avoiding, or recovering from the issue. It might not be a permanent solution. The work-around is unnecessary, as the version of code for which this release note is documented has resolved the issue.

Fixed S3048–ON 9.14(1.10) Software Issues

 **NOTE:** Dell EMC Networking OS 9.14(1.10) includes fixes for issues addressed in previous 9.14 releases. Refer to the respective release notes documentation for the list of issues fixed in earlier 9.14 releases.

The following issues are fixed in Dell EMC Networking OS version 9.14(1.10):

PR#170115

Severity:	Sev 3
Synopsis:	The switch may encounter an exception when an incorrect length field is specified in a TACACS packet.
Release Notes:	The switch may encounter an exception when an incorrect length field is specified in a TACACS packet.
Workaround:	None

PR#170159

Severity:	Sev 3
Synopsis:	SSH connections with Cipher Block Chaining (CBC) ciphers are vulnerable.
Release Notes:	SSH connections with Cipher Block Chaining (CBC) ciphers are vulnerable.
Workaround:	Configure a stronger Cipher/MAC/KEX setting using the <code>ip ssh server</code> command.

PR#170161

Severity:	Sev 2
Synopsis:	SSH connections may be vulnerable with switches running on a 1024 bit RSA key.
Release Notes:	SSH connections may be vulnerable with switches running on a 1024 bit RSA key.
Workaround:	Create a new 2048 bit RSA key using the <code>crypto key generate rsa</code> command.
PR#170206	
Severity:	Sev 2
Synopsis:	Addressed OpenSSL CVE's: CVE-2021-3711 and CVE-2021-3712.
Release Notes:	The following CVEs have been addressed: <ul style="list-style-type: none"> • CVE-2021-3711 • CVE-2021-3712 The CVE database can be accessed here: https://cve.mitre.org/cve/search_cve_list.html .
Workaround:	None
PR#170211	
Severity:	Sev 2
Synopsis:	When a switch with scaled VLANs is reloaded, traffic drop may occur due to a delay in VLAN programming.
Release Notes:	When a switch with scaled VLANs is reloaded, traffic drop may occur due to a delay in VLAN programming.
Workaround:	None

Known Issues

Known issues are reported using the following definitions.

Category	Description
PR#	Problem Report number that identifies the issue.
Severity	<p>S1 — Crash: A software crash occurs in the kernel or a running process that requires a restart of AFM, the router, switch, or process.</p> <p>S2 — Critical: An issue that renders the system or a major feature unusable, which can have a pervasive impact on the system or network, and for which there is no work-around acceptable to the customer.</p> <p>S3 — Major: An issue that affects the functionality of a major feature or negatively effects the network for which there exists a work-around that is acceptable to the customer.</p> <p>S4 — Minor: A cosmetic issue or an issue in a minor feature with little or no network impact for which there might be a work-around.</p>
Synopsis	Synopsis is the title or short description of the issue.
Release Notes	Release Notes description contains more detailed information about the issue.
Work around	Work around describes a mechanism for circumventing, avoiding, or recovering from the issue. It might not be a permanent solution.

Category Description

Issues listed in the "Fixed Issues" section should not be present, and the work-around is unnecessary, as the version of code for which this release note is documented has resolved the issue.

Known S3048-ON 9.14(1.10) Software Issues

The following caveats are open in Dell EMC Networking OS version 9.14(1.10):

PR#169841

Severity:	Sev 2
Synopsis:	In certain scenarios, an MSDP learnt PIM TIB entry stays in registering state indefinitely.
Release Notes:	In certain scenarios, an MSDP learnt PIM TIB entry stays in registering state indefinitely.
Workaround:	Set the affected node as a non-designated router in the RPF neighbor interface.

Upgrading ONIE on the S3048-ON

To upgrade the ONIE package you have installed, use one of the following two processes: zero touch (dynamic) update or manual update.

1. Zero touch (dynamic): Copy the update ONIE installer and the DIAG installer for your system to the TFTP/HTTP server. Configure the DHCP options using the ONIE specifications shown at the following link: <http://opencomputeproject.github.io/onie/docs/design-spec/updater.html>
S3048-ON image>>>> onie-updater-x86_64-s3000_c2338-r0
2. Manual: Copy the image onto the TFTP/HTTP servers and boot ONIE. Update the ONIE using the **onie-self-update** command, then download and run an ONIE updater image. The supported URL types are: HTTP, FTP, TFTP, and FILE.
S3048-ON image>>>> onie-updater-x86_64-s3000_c2338-r0
3. UPGRADING ONIE ON AN EXISTING S3048-ON SYSTEM.

The following example uses HTTP to upgrade ONIE.

```
ONIE:/ # onie-self-update tftp://10.16.127.35/onie-updater-x86_64-s3000_c2338-r0
Stopping: discover... done.
Info: Fetching tftp://10.16.127.35/onie-updater-x86_64-s3000_c2338-r0 ...
onie-updater-x86_64- 100% |*****| 9021k 0:00:00 ETA
ONIE: Executing installer: tftp://10.16.127.35/onie-updater-x86_64-s3000_c2338-r0
Verifying image checksum ... OK.
Preparing image archive ... OK.
ONIE: Version      : 3.24.1.0-4
ONIE: Architecture : x86_64
ONIE: Machine      : s3000_c2338
ONIE: Machine Rev  : 0
ONIE: Config Version: 1
Installing ONIE on: /dev/sda
Rebooting...
ONIE:/ # umount: can't remount rootfs read-only
The system is going down NOW!
Sent SIGTERM to all processes
Sent SIGKILL tosd 0:0:0:0: [sda] Synchronizing SCSI cache
Restarting system.
machine restart
```

4. Upgrade the DIAG installer package.

```
ONIE:/ # onie-nos-install tftp://10.16.127.35/INSTALLER-DND-SG-2.0.0.4.bin
Stopping: discover... done.
Info: Fetching tftp://10.16.127.35/INSTALLER-DND-SG-2.0.0.4.bin ...
INSTALLER-DND-SG-2.0 100% |*****| 27956k 0:00:00 ETA
ONIE: Executing installer: tftp://10.16.127.35/INSTALLER-DND-SG-2.0.0.4.bin
Verifying image checksum ... OK.
Preparing image archive from /installer ... Done.
Mounting /dev/sda3...Done.
Copying Images ...Done.
Installing Menu Entry ...Done.
ONIE:/ # umount: can't remount rootfs read-only
The system is going down NOW!
Sent SIGTERM to all processes
Sent SIGKILL tosd 0:0:0:0: [sda] Synchronizing SCSI cache
Restarting system.
machine restart
```

5. Upgrade the BIOS image using the BIOS image and Flashrom utility included with the diagnostic package.

```
ONIE:/ #
ONIE:/ # tftp -g -r s3000-bios-3.24.0.0-11.bin 10.16.127.35
s3000-bios-3.24.0.0-11. 100% |*****| 8192k 0:00:00 ETA
ONIE:/ #
ONIE:/ # flashrom -E -p internal
Erasing and writing flash chip... Erase/write done.
ONIE:/ #
ONIE:/ #
ONIE:/ # flashrom -w s3000-bios-3.24.0.0-11.bin -p internal
Erasing and writing flash chip... Erase/write done.
Verifying flash... VERIFIED.
ONIE:/ #
ONIE:/ #
ONIE:/ # reboot
ONIE:/ # umount: can't remount rootfs read-only
The system is going down NOW!
Sent SIGTERM to all processes
Sent SIGKILL tosd 0:0:0:0: [sda] Synchronizing SCSI cache
Restarting system.
machine restart

BIOS (Dell EMC Inc) Boot Selector
S3000 3.24.0.0-11
(48-port 1G/4-port SFP+ 10G)

CPLD JTAG to normal mode... done.
Resetting...
```

Installing Dell EMC Networking OS on the S3048-ON using ONIE

 **NOTE:** The Dell EMC Networking OS installer package, ONIE-FTOS-SG-ON-9.14.1.10.bin, is required for installing Dell EMC Networking OS on S3048-ON that has only ONIE.

To install the Dell EMC Networking OS version 9.14(1.10) on to the new S3048-ON device, perform the following steps:

1. Boot the system to the ONIE prompt. The following ONIE prompt appears:

```
ONIE:/ #
```

2. Stop the ONIE discovery process using the following command:

```
ONIE:/ # onie-discovery-stop
```

The following message appears:

```
Stopping: discover... done.  
ONIE:/ #
```

3. Configure an interface and assign an IP address to that interface using the following command:

```
ONIE:/ # ifconfig eth0 ip-address/prefix up
```

4. Enter the following command to begin the installation process:

```
ONIE:/ # onie-nos-install tftp://10.16.127.35/ONIE-FTOS-SG-ON-9.14.1.10.bin
```

i **NOTE:** After the Dell EMC Networking OS installation is complete, the system automatically reboots.

Following is the installation and boot log of Dell EMC Networking OS:

```
ONIE:/ # onie-nos-install tftp://10.16.127.35/ONIE-FTOS-SG-9.14.1.10.bin  
Stopping: discover... done.  
Info: Fetching tftp://10.16.127.35/ONIE-FTOS-SG-9.14.1.10.bin ...  
ONIE-FTOS-SG-9.14.1.10 100% |*****| 95426k 0:00:00 ETA  
ONIE: Executing installer: tftp://10.16.127.35/ONIE-FTOS-SG-9.14.1.10.bin  
Verifying image checksum ... OK.  
Preparing image archive from /installer ... Done.  
Verifying Product Platform...  
Image File           : ONIE-FTOS-SG-9.14.1.10.bin  
Product Name        : S3048-ON  
Platform Verified   : OK  
Deleting Extra partitions... Done.  
Creating New partitions... Done.  
Creating Hybrid MBR... Done.  
Mounting /dev/sda4,/dev/sda5 and /dev/sda6... Done.  
Installing GRUB on /dev/sda4...Done.  
Copying Images... Done.  
ONIE:/ # umount: can't remount rootfs read-only  
The system is going down NOW!  
Sent SIGTERM to all processes  
Sent SIGKILL tosd 0:0:0:0: [sda] Synchronizing SCSI cache  
Restarting system.  
machine restart  
  
BIOS (Dell EMC) Boot Selector  
S3000 3.24.0.0-11  
(48-port 1G/4-port SFP+ 10G)  
  
CPLD JTAG to normal mode... done.  
Resetting...  
  
POST Configuration  
CPU Signature 406D8  
CPU FamilyID=6, Model=4D, SteppingId=8, Processor=0  
Microcode Revision 125  
Platform ID: 0x1004183D  
PMG_CST_CFG_CTL: 0x40006  
BBL_CR_CTL3: 0x7E2801FF  
Misc EN: 0x4000840081  
Gen PM Con1: 0x1008  
Therm Status: 0x88490000  
POST Control=0xEA010303, Status=0xE6009601  
  
BIOS initializations...  
  
CPLD JTAG to normal mode... done.  
  
BIOS initializations...  
  
CPGC Memtest for Channel 0 ..... PASS  
ECC enabled: channel 0 DECCCTRL_DUNIT_REG=0x000200F3
```



```

POST:
  RTC Battery OK at last cold boot
  RTC date Friday 09/24/2021 22:35:26

POST SPD test ..... PASS

POST Lower DRAM Memory test
  Short memory cell test
  Perf cnt (curr, fixed): 0x21157AA35, 0x31A008980

POST Lower DRAM Memory test ..... PASS
POST Lower DRAM ECC check ..... PASS

Dell DxE configurations...
Broadcom Preemphasis...
  Gen1=0x4, Gen2=0x43
done.
NPU CDR... .. done.
SM Bus1 PHY...done

DxE POST
POST PCI test ..... PASS
POST NVRAM check ..... PASS
POST overall test results ..... PASS

Version 2.16.1242. Copyright (C) 2020 American Megatrends, Inc.
BIOS Date: 09/24/2021 15:25:58 Ver: 0ACBZ018
Press DEL or F2 to enter setup.

Grub 1.99~rc1 (Dell EMC)
Built by root at ubuntu on Fri_Sep_24_08:53:42_UTC_2021
S3000ON Boot Flash Label 3.24.2.9 NetBoot Label 3.24.2.9

Press Esc to stop autoboot ... 0

Primary Boot  not Configured

Secondary Boot  not Configured

Bootting DEFAULT configuration...

boot device          : flash
file                 : systema (Dell EMC Networking OS system://A
Partition)
Copyright (c) 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005,
2006, 2007, 2008, 2009, 2010
The NetBSD Foundation, Inc. All rights reserved.
Copyright (c) 1982, 1986, 1989, 1991, 1993
The Regents of the University of California. All rights reserved.

Dell EMC Networking OS Release 9.14(1.10)
NetBSD 5.1_STABLE (S3000) #0: Fri Sep 24 03:39:56 PDT 2021

```

5. After the installation completes, the system displays the following DELL EMC prompt:
DellEMC>

Upgrading the S3048-ON Dell EMC Networking OS Image using the Dell EMC Networking OS CLI

Bare Metal Provisioning

NOTE: If you are using Bare Metal Provisioning (BMP), see the Bare Metal Provisioning topic in the Dell EMC Networking OS Configuration Guide or the Open Automation Guide.

Manual Upgrade Procedure

Follow these steps carefully to upgrade your S3048-ON systems:

1. Dell EMC Networking recommends that you back up your startup configuration and any important files and directories to an external media prior to upgrading the system.

NOTE: If you are upgrading from Dell EMC Networking OS version 9.10.0.1P5 or earlier, you cannot directly upgrade to version 9.14(1.10). Upgrade to version 9.10(0.1P8) first and then upgrade to the required version.

2. Upgrade the Dell EMC Networking OS in flash partition A: or B:

```
upgrade system [flash: | ftp: stack-unit <1-6> | tftp: | scp: | usbflash:] [A: | B:]
```

EXEC Privilege

```
DellEMC#upgrade system tftp: a:
Address or name of remote host []: 10.16.127.35
Source file name []: FTOS-SG-9.14.1.10.bin
3d17h59m : Discarded 1 pkts. Expected block num : 62. Received block num: 61
3d17h59m : Discarded 1 pkts. Expected block num : 65. Received block num: 64
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
.....!
62620397 bytes successfully copied
System image upgrade completed successfully.
DellEMC#Sep 24 11:56:43: %STKUNIT1-M:CP %DOWNLOAD-6-UPGRADE: Upgrade completed
successfully
DellEMC#

DellEMC#upgrade system tftp: b:
Address or name of remote host []: 10.16.127.35
Source file name []: FTOS-SG-9.14.1.10.bin
3d18h2m : Discarded 1 pkts. Expected block num : 51. Received block num: 50
3d18h2m : Discarded 1 pkts. Expected block num : 65. Received block num: 64
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
.....!
62620397 bytes successfully copied
System image upgrade completed successfully.
DellEMC#Sep 24 12:00:33: %STKUNIT1-M:CP %DOWNLOAD-6-UPGRADE: Upgrade completed
successfully
DellEMC#
```

3. Verify that the Dell EMC Networking OS has been upgraded correctly in the upgraded flash partition

```
show boot system stack-unit [1-6] | all]
```

EXEC Privilege

```
DellEMC#show boot system stack-unit all

Current system image information in the system:
=====
Type           Boot Type      A                               B
-----
stack-unit 1  DOWNLOAD BOOT  9.14(1.10)[boot]             9.14(1.9P4)
stack-unit 2  is not present.
stack-unit 3  is not present.
stack-unit 4  is not present.
stack-unit 5  is not present.
stack-unit 6  is not present.
DellEMC#
DellEMC#
```

4. Change the Primary Boot Parameter of the S3048-ON to the upgraded partition A: or B:

```
boot system stack-unit 1 primary system: [A: | B: | tftp: | ftp:]
```

CONFIGURATION

5. Save the configuration so that the configuration will be retained after a reload using write memory command.

```
write [memory]
```

EXEC PRIVILEGE

```
DellEMC#write memory
!
Sep 24 18:58:59: %STKUNIT1-M:CP %FILEMGR-5-FILESAVED: Copied running-config to
startup-config in flash by default

DellEMC#
```

6. Reload the unit

```
reload
```

EXEC PRIVILEGE

```
Command      : reload
Mode         : EXEC PRIVILEGE
DellEMC#reload
Proceed with reload [confirm yes/no]: y
```

7. Verify the S3048 ON has been upgraded to the Dell EMC Networking OS version 9.14(1.10)

```
show version
```

EXEC PRIVILEGE

```
DellEMC#show version
Dell EMC Real Time Operating System Software
Dell EMC Operating System Version: 2.0
Dell EMC Application Software Version: 9.14(1.10)
Copyright (c) 1999-2021 by Dell Inc. All Rights Reserved.
Build Time: Fri Sep 24 10:20:04 2021
Build Path: /build/build01/SW/SRC
Dell EMC Networking OS uptime is 3 day(s), 21 hour(s), 3 minute(s)

System image file is "system://A"


System Type: S3048-ON
Control Processor: Intel Rangeley with 2 Gbytes (2127654912 bytes) of memory, core(s)
2.

8G bytes of boot flash memory.

 1 52-port GE/TE (SG-ON)
48 GigabitEthernet/IEEE 802.3 interface(s)
 4 Ten GigabitEthernet/IEEE 802.3 interface(s)
DellEMC#
```

Upgrading the CPLD

The S3048-ON system with Dell EMC Networking OS Version 9.14(1.10) requires System CPLD revision 9 and Module CPLD revision 7.

 **NOTE:** If your CPLD revisions are higher than the ones shown here, DO NOT make any changes. If you have questions regarding the CPLD revision, contact technical support.

Verify that a CPLD upgrade is required

Use the following command to identify the CPLD version:

```
DellEMC#show revision

-- Stack unit 1 --
S3048-ON SYSTEM CPLD      : 9
S3048-ON MODULE CPLD     : 7
```



```

!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!

Upgrade result :
=====
Unit 1 FPGA upgrade successful. Power cycle the Unit 1 to complete the upgrade.

DellEMC#00:04:11: %S3048-ON:1 %DOWNLOAD-6-FPGA_UPGRADE: stack-unit 1 fpga upgrade
success.

DellEMC#

Need to power cycle the unit to complete the FPGA upgrade.

```

2. Power cycle the system physically. Switch off the system by unplugging the power chords from the REAR PSUs and wait until the PSU FAN-REAR STATUS LED is completely OFF.

i | **NOTE:** Do not switch on the system with PSU-REAR LED glowing AMBER.

You can alternatively power cycle the switch using the `power-cycle stack-unit <1-6>` command as follows:

```

DellEMC#power-cycle stack-unit 1
Proceed with power-cycle? Confirm [yes/no]:yes

```

3. The CPLD version can be verified using show revision command output :

```

show revision
EXEC PRIVILEGE

```

```

DellEMC#show revision

-- Stack unit 1 --
S3048-ON SYSTEM CPLD      : 9
S3048-ON MODULE CPLD     : 7

DellEMC#

```

i | **NOTE:** Do not power off the system while FPGA upgrade is in progress. For any queries, contact technical support.

Upgrade the BIOS from Dell EMC Networking OS

To upgrade the BIOS from Dell EMC Networking OS, perform the following steps:

1. Upgrade the S3048-ON Boot Flash image.

```

upgrade boot bootflash-image stack-unit [<id> | all] [booted | flash: | ftp: | scp: |
tftp: | usbflash:]

```

EXEC Privilege

```

DellEMC#upgrade boot bootflash-image stack-unit 1 booted

Current Boot information in the system:
=====
Card                BootFlash          Current Version    New Version
-----
Unit1               Boot Flash         3.24.2.3           3.24.2.9

*****
* Warning - Upgrading boot flash is inherently risky and should only *
* be attempted when necessary. A failure at this upgrade may cause *
* a board RMA. Proceed with caution !                               *
*****

Proceed upgrade Boot Flash image for stack-unit 1 [yes/no]: yes

```

```
!!!!
Bootflash image upgrade for stack-unit 1 completed successfully.
```

2. Upgrade the S3048-ON Boot Selector image.

```
upgrade boot bootselector-image stack-unit [<id> | all] [booted | flash: | ftp: | scp: |
tftp: | usbflash:]
```

EXEC Privilege

Dell EMC Networking OS version 9.14(1.10) requires S3048-ON Boot Selector image version 3.24.0.0-11. The booted option is used to upgrade the Boot Selector image to the image version packed with the loaded Dell EMC Networking OS image. The Boot Selector image version packed with the loaded Dell EMC Networking OS can be found using the **show os-version** command in EXEC Privilege mode.

```
DellEMC#upgrade boot bootselector-image stack-unit 1 booted

Current Boot information in the system:
=====
Card                BootSelector        Current Version      New Version
-----
Unit1                Boot Selector       3.24.0.0-9          3.24.0.0-11

*****
* Warning - Upgrading boot selectors is inherently risky and should *
* only be attempted when necessary. A failure at this upgrade may   *
* cause a board RMA. Proceed with caution !                          *
*****

Proceed upgrade Boot Selector image for stack-unit 1 [yes/no]: yes

!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!00:02:33: %S3048-ON:1 %CHMGR-2-
FAN_SPEED_CHANGE: Fan speed changed to 52 % of the full speed
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Bootselector image upgrade for stack-unit 1 completed successfully.
DellEMC#
```

3. Reload the unit

```
reload
```

EXEC Privilege

4. Verify the Boot Selector image

```
show system stack-unit <id>
```

EXEC Privilege

```
DellEMC#show system stack-unit 1

-- Unit 1 --
Unit Type           : Management Unit
Status              : online
Next Boot           : online
Required Type       : S3048-ON - 52-port GE/TE (SG-ON)
Current Type        : S3048-ON - 52-port GE/TE (SG-ON)
Master priority     : 0
Hardware Rev        : 0.0
Num Ports           : 52
Up Time             : 13 min, 15 sec
Dell EMC Networking OS Version : 9.14(1.10)
Jumbo Capable       : yes
POE Capable         : no
FIPS Mode           : disabled
Boot Flash          : 3.24.2.9
Boot Selector       : 3.24.0.0-11

Memory Size         : 2127654912 bytes
Temperature         : 30C
Voltage             : ok
Serial Number       : NA
Part Number         : 0VCY6T      Rev A00
Vendor Id           : NA
```

```

Date Code           : NA
Country Code        : NA
Piece Part ID       : CN-123456-DELLI-215-8989
PPID Revision       : A00
Service Tag         : NA
Expr Svc Code       : NA
Auto Reboot         : enabled
Burned In MAC       : 00:e0:ec:25:d9:50
No Of MACs          : 3

-- Power Supplies --
Unit   Bay   Status   Type   FanStatus  FanSpeed (rpm)
-----
  1     1    up       AC     up         8032
  1     2    up       AC     up         8096

-- Fan Status --
Unit Bay   TrayStatus  Fan1   Speed
-----
  1   1     up          up     7200
  1   2     up          up     7200
  1   3     up          up     7200

Speed in RPM
DellEMC#

```

Uninstalling Dell EMC Networking OS on the S3048-ON

To uninstall the Dell EMC Networking OS version 9.14(1.10) from the S3048-ON device, perform the following steps:

1. Reboot the system. During the reboot process, the system displays the following message prompting you to press the Esc key in order to stop the auto-boot process:

```

Version 2.16.1242. Copyright (C) 2020 American Megatrends, Inc.
BIOS Date: 09/24/2021 15:25:58 Ver: 0ACBZ018
Press DEL or F2 to enter setup.

Grub 1.99~rc1 (Dell EMC)
Built by root at ubuntu on Fri_Sep_24_08:53:42_UTC_2021
S3000ON Boot Flash Label 3.24.2.9 NetBoot Label 3.24.2.9

Press Esc to stop autoboot ... 5

```

2. At this prompt message, press the Esc key. The following menu appears:

```

+-----+
| Dell EMC Networking OS
| Dell EMC-Boot Line Interface
| DELL-DIAG
| ONIE
+-----+

```

3. From the menu, choose the **ONIE** option.

NOTE: To choose an option from the menu, highlight one of the options using the up or down arrow key and press **Enter**.

The following menu appears:

```

+-----+
| ONIE: Install OS
| ONIE: Rescue
| *ONIE: Uninstall OS
| ONIE: Update ONIE
| ONIE: Embed ONIE
| ONIE: Diag ONIE
+-----+

```

4. From this menu, choose the **ONIE : Uninstall OS** option.

NOTE: To choose an option from the menu, highlight one of the options using the up or down arrow key and press Enter.

The uninstall process begins. Following is the log generated by the system while Dell EMC Networking OS 9.14(1.10) uninstalls:

```
ONIE: OS Uninstall Mode ...
Version   : 3.24.1.0-4
Build Date: 2021-09-24T13:53-0700
Info: Mounting kernel filesystems... done.
Info: Mounting LABEL=ONIE-BOOT on /mnt/onie-boot ...
Info: Using eth0 MAC address: 00:85:13:53:99:10
Info: Using eth1 MAC address: 00:85:13:53:99:11
Info: eth0: Checking link... up.
Info: Trying DHCPv4 on interface: eth0
DHCPv4 on interface: eth0 failedONIE: Using default IPv4 addr: eth0:
192.168.3.10/255.255.255.0
Info: eth1: Checking link... down.
ONIE: eth1: link down. Skipping configuration.
ONIE: Failed to configure eth1 interface
Starting: dropbear ssh daemon... done.
Starting: telnetd... done.
discover: Uninstall mode detected. Running uninstaller.
Erasing internal mass storage device: /dev/sda3 (300MB)
  Percent complete: 100%
Erase complete.
Deleting partition 3 from /dev/sda
Erasing internal mass storage device: /dev/sda4 (32MB)
  Percent complete: 100%
Erase complete.
Deleting partition 4 from /dev/sda
Erasing internal mass storage device: /dev/sda5 (300MB)
  Percent complete: 100%
Erase complete.
Deleting partition 5 from /dev/sda
Erasing internal mass storage device: /dev/sda6 (300MB)
  Percent complete: 100%
Erase complete.
Deleting partition 6 from /dev/sda
Erasing internal mass storage device: /dev/sda7 (6578MB)
  Percent complete: 100%
Erase complete.
Deleting partition 7 from /dev/sda
Installing for i386-pc platform.
Installation finished. No error reported.
Uninstall complete. Rebooting...
umount: can't remount rootfs read-only
The system is going down NOW!
Sent SIGTERM to all processes
Sent SIGKILL to all processes
Requesting system reboot
sd 0:0:0:0: [sda] Synchronizing SCSI cache
Restarting system.
machine restart

BIOS (Dell EMC) Boot Selector
S3000 3.24.0.0-11
(48-port 1G/4-port SFP+ 10G)

CPLD JTAG to normal mode... done.
Resetting...

POST Configuration
CPU Signature 406D8
CPU FamilyID=6, Model=4D, SteppingId=8, Processor=0
Microcode Revision 125
```



```
Platform ID: 0x1004183D
PMG_CST_CFG_CTL: 0x40006
BBL_CR_CTL3: 0x7E2801FF
Misc EN: 0x4000840081
Gen PM Con1: 0x1008
Therm Status: 0x884B0000
POST Control=0xEA010303, Status=0xE6009601
```

```
BIOS initializations...
```

```
CPLD JTAG to normal mode... done.
```

```
BIOS initializations...
```

```
CPGC Memtest for Channel 0 ..... PASS
```

```
ECC enabled: channel 0 DECCCTRL_DUNIT_REG=0x000200F3
```

5. After the installation completes, the system displays the following ONIE prompt:

```
ONIE:/ #
```

Installing a Third Party Operating System

Apart from the Dell EMC Networking OS, you can also install a supported third party operating system on the S3048-ON system. For more information on installing a third party operating system, please check the ONIE documentation at <https://github.com/opencomputeproject/onie/wiki/Quick-Start-Guide> and refer to the respective third party OS vendor's website for OS installation instructions.

Support Resources

The following support resources are available for the S3048-ON system.

Documentation Resources

This document contains operational information specific to the S3048-ON system.

For information about using the S3048-ON, refer to the following documents at <http://www.dell.com/support>:

- *Installing the S3048-ON System*
- *Quick Start Guide*
- *Dell EMC Networking Command Line Reference Guide for the S3048-ON System*
- *Dell EMC Networking Configuration Guide for the S3048-ON System*

For more information about hardware features and capabilities, refer to the Dell EMC Networking website at <https://www.dellemc.com/networking>.

For more information about the open network installation environment (ONIE)-compatible third-party operating system, refer to <http://onie.org>.

Issues

Issues are unexpected or incorrect behavior and are listed in order of Problem Report (PR) number within the appropriate sections.


Finding Documentation

This document contains operational information specific to the S3048-ON system.

- For information about using the S3048-ON, refer to the documents at <http://www.dell.com/support>.
- For more information about hardware features and capabilities, refer to the Dell EMC Networking website at <https://www.dellemc.com/networking>.

- For more information about the open network installation environment (ONIE)-compatible third-party operating system, refer to <http://onie.org>.


Contacting Dell EMC

 **NOTE:** If you do not have an active Internet connection, you can find contact information on your purchase invoice, packing slip, bill, or Dell EMC product catalog.

Dell EMC provides several online and telephone-based support and service options. Availability varies by country and product, and some services may not be available in your area. To contact Dell EMC for sales, technical support, or customer service issues:

Go to www.dell.com/support.

Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.