

S5200-ON Series BMC User Guide

September 2018

Notes, cautions, and warnings

 **NOTE:** A NOTE indicates important information that helps you make better use of your product.

 **CAUTION:** A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

 **WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

Copyright © 2018 Dell Inc. or its subsidiaries. All rights reserved. Dell, EMC, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

1 About this guide	5
Information symbols.....	5
Document revision history.....	5
2 Hardware and software support	6
Required drivers.....	6
BMC access.....	6
3 Configuration methods	7
Configurations.....	12
LAN configurations.....	12
DNS configuration.....	13
Date and time.....	13
SNMP and email alerts.....	13
Event filters.....	13
Alert policies and destinations.....	14
LAN destinations.....	15
Alert policy setup.....	16
Add and delete users.....	16
Set User Name Command.....	19
Set User Password Command.....	19
Firewall.....	20
Event log.....	35
Reserve system event log (SEL) command.....	35
Get SEL command.....	36
Set LOG configuration command.....	36
Audit log configuration.....	36
Default configuration Restore.....	37
Restore default configuration command.....	37
Set backup configuration flag.....	37
4 Firmware update	39
5 Host power control	40
6 Access system health sensors	41
ipmitool sensors.....	41
7 Access FRU data	44
ipmitool FRUs.....	44
8 ipmiutil package	46

9 Dell EMC support.....47

About this guide

This guide provides information for using the Dell EMC baseboard management controller (BMC).

⚠ CAUTION: To avoid electrostatic discharge (ESD) damage, wear grounding wrist straps when handling this equipment.

⚠ WARNING: Only trained and qualified personnel can install this equipment. Read this guide before you install and power up this equipment. This equipment contains two power cords. Disconnect both power cords before servicing.

⚠ WARNING: This equipment contains optical transceivers, which comply with the limits of Class 1 laser radiation.



Figure 1. Class 1 laser product tag

⚠ WARNING: When no cable is connected, visible and invisible laser radiation may be emitted from the aperture of the optical transceiver ports. Avoid exposure to laser radiation. Do not stare into open apertures.

Topics:

- [Information symbols](#)
- [Document revision history](#)

Information symbols

This book uses the following information symbols:

ⓘ NOTE: The Note icon signals important operational information.

⚠ CAUTION: The Caution icon signals information about situations that could result in equipment damage or loss of data.

⚠ WARNING: The Warning icon signals information about hardware handling that could result in injury.

⚠ WARNING: The ESD Warning icon requires that you take electrostatic precautions when handling the device.

Document revision history

Table 1. Revision history

Revision	Date	Description
A00	2018-09	Initial release

Hardware and software support

For the most current BMC update information, see the *S5200-ON Series Release Notes*.

For more information about the intelligent platform management interface (IPMI), see the IPMI resources that is hosted by Intel at <https://www.intel.com/content/www/us/en/servers/ipmi/ipmi-technical-resources.html>.

Required drivers

In Linux, the baseboard management controller (BMC) uses the `ipmitool` open-source tool during testing. To configure or get data from the BMC, `ipmitool` sends `ipmi` commands to the BMC. You must have the IPMI driver installed to use `ipmitool`.

To access `ipmitools`, go to <https://sourceforge.net>, search for `ipmitools`, then select the **See Project** button.

NOTE: Although there are newer versions available, the `ipmitool` and driver versions used during testing the BMC are:

- Linux version: 4.9.30
- `ipmitool` version: 1.8.18
- `ipmi` driver that the `ipmitool` uses is built with kernel 4.9.30.

BMC access

Access BMC through the network interface from a remote machine. Use `ipmitool` for host and remote access.

- LAN interface—`ipmitool` is the standard tool to access BMC over the network. A dummy static IP address is preprogrammed in the BMC. You can change this dummy static IP address of the network interface using `ipmitool` from the microprocessor console:
 - `# ipmitool lan set 1 ipaddr <x.x.x.x>`

Configuration methods

The diagnostic operating software (DIAG OS) running on the local processor has `ipmitool` installed by default. You can use the `ipmitool` both at the switch and remotely.

Accessing BMC from the host does not require user name or password. The general syntax for using `ipmitool` is:

NOTE: `-I` and `-H` are optional.

```
ipmitool [-c|-h|-v|-V] [-I lanplus -H <hostname> [-p <port>]
[-U <username>]
[-L <privlvl>]
[-a|-E|-P|-f <password>]
[-o <oemtype>]
[-O <sel oem>]
[-C <ciphersuite>]
[-Y|[-K|-k <kg_key>]
[-y <hex_kg_key>]
[-e <esc_char>]
[-N <sec>]
[-R <count>]
< command>
```

For example, to list sensors from the host use the following command from the host:

```
root@dellemc-diag-os:~# ipmitool sensor
PT_Mid_temp | 31.000 | degrees C | ok | na | na | na | 78.000 |
80.000 | 85.000
NPU_Near_temp | 29.000 | degrees C | ok | na | na | na | na |
na | na
PT_Left_temp | 28.000 | degrees C | ok | na | na | na | na |
na | na
PT_Right_temp | 30.000 | degrees C | ok | na | na | na | na |
na | na
ILET_AF_temp | 26.000 | degrees C | ok | na | na | na | na |
na | na
PSU1_AF_temp | 24.000 | degrees C | ok | na | na | na | 61.000 |
64.000 | na
PSU2_AF_temp | 25.000 | degrees C | ok | na | na | na | na |
na | na
PSU1_temp | 34.000 | degrees C | ok | na | na | na | na |
na | na
PSU2_temp | na | degrees C | na | na | na | na | na |
na | na
CPU_temp | 31.000 | degrees C | ok | na | na | na | 90.000 |
94.000 | na
FAN1_Rear_rpm | 9120.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN2_Rear_rpm | 9000.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN3_Rear_rpm | 9000.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN4_Rear_rpm | 9120.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN1_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN2_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN3_Front_rpm | 9960.000 | RPM | ok | na | 1080.000 | na | na |
na | na
```

FAN4_Front_rpm	10080.000	RPM	ok	na	1080.000	na	na	
na	na							
PSU1_rpm	9000.000	RPM	ok	na	na	na	na	
na	na							
PSU2_rpm	na	RPM	na	na	na	na	na	
na	na							
PSU_Total_watt	110.000	Watts	ok	na	na	na	na	
na	na							
PSU1_stat	0x0	discrete	0x0180	na	na	na	na	
na	na							
PSU2_stat	0x0	discrete	0x0380	na	na	na	na	
na	na							
PSU1_In_watt	110.000	Watts	ok	na	na	na	na	
na	na							
PSU1_In_volt	205.700	Volts	ok	na	na	na	na	
na	na							
PSU1_In_amp	0.480	Amps	ok	na	na	na	na	
na	na							
PSU1_Out_watt	90.000	Watts	ok	na	na	na	na	
na	na							
PSU1_Out_volt	12.400	Volts	ok	na	na	na	na	
na	na							
PSU1_Out_amp	7.500	Amps	ok	na	na	na	na	
na	na							
PSU2_In_watt	na	Watts	na	na	na	na	na	
na	na							
PSU2_In_volt	na	Volts	na	na	na	na	na	
na	na							
PSU2_In_amp	na	Amps	na	na	na	na	na	
na	na							
PSU2_Out_watt	na	Watts	na	na	na	na	na	
na	na							
PSU2_Out_volt	na	Volts	na	na	na	na	na	
na	na							
PSU2_Out_amp	na	Amps	na	na	na	na	na	
na	na							
ACPI_stat	0x0	discrete	0x0180	na	na	na	na	
na	na							
FAN1_prsnt	0x0	discrete	0x0180	na	na	na	na	
na	na							
FAN2_prsnt	0x0	discrete	0x0180	na	na	na	na	
na	na							
FAN3_prsnt	0x0	discrete	0x0180	na	na	na	na	
na	na							
FAN4_prsnt	0x0	discrete	0x0180	na	na	na	na	
na	na							
FAN1_Rear_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN2_Rear_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN3_Rear_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN4_Rear_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN1_Front_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN2_Front_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN3_Front_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
FAN4_Front_stat	0x0	discrete	0x0080	na	na	na	na	
na	na							
INTER_5.0V_volt	4.900	Volts	ok	4.200	4.500	4.700	5.200	
5.500	5.700							
INTER_3.3V_volt	3.300	Volts	ok	2.800	3.000	3.100	3.500	
3.600	3.800							
FPGA_1.0V_volt	0.990	Volts	ok	0.850	0.900	0.950	1.050	
1.100	1.150							
FPGA_1.2V_volt	1.190	Volts	ok	1.020	1.080	1.140	1.260	


```

1.320 | 1.380
FPGA_1.8V_volt | 1.780 | Volts | ok | 1.530 | 1.620 | 1.710 | 1.890 |
1.980 | 2.070
FPGA_3.3V_volt | 3.200 | Volts | ok | 2.800 | 3.000 | 3.100 | 3.500 |
3.600 | 3.800
BMC_2.5V_volt | 2.400 | Volts | ok | 2.100 | 2.200 | 2.300 | 2.600 |
2.800 | 2.900
BMC_1.15V_volt | 1.150 | Volts | ok | 0.980 | 1.030 | 1.090 | 1.210 |
1.270 | 1.320
BMC_1.2V_volt | 1.210 | Volts | ok | 1.020 | 1.080 | 1.140 | 1.260 |
1.320 | 1.380
SWITCH_6.8V_volt | 7.000 | Volts | ok | 5.800 | 6.100 | 6.400 | 7.200 |
7.500 | 7.800
SWITCH_3.3V_volt | 3.300 | Volts | ok | 2.800 | 3.000 | 3.100 | 3.500 |
3.600 | 3.800
SWITCH_1.8V_volt | 1.790 | Volts | ok | 1.530 | 1.620 | 1.710 | 1.890 |
1.980 | 2.070
USB_5.0V_volt | 4.900 | Volts | ok | 4.200 | 4.500 | 4.700 | 5.200 |
5.500 | 5.700
NPU_1.2V_volt | 1.190 | Volts | ok | 1.020 | 1.080 | 1.140 | 1.260 |
1.320 | 1.380
NPU_VDDCORE_volt | 0.800 | Volts | ok | 0.700 | 0.720 | 0.740 | 0.910 |
0.930 | 0.950
NPU_VDDANLG_volt | 0.790 | Volts | ok | 0.680 | 0.720 | 0.760 | 0.840 |
0.880 | 0.920
BMC_boot | 0x0 | discrete | 0x0180 | na | na | na | na |
na | na
SEL_sensor | 0x0 | discrete | 0x1080 | na | na | na | na |
na | na

```

The command parameters change slightly when using ipmitool over LAN:

```
root@dellmc-diag-os:~# ipmitool -U admin -P admin -I lanplus -H 10.11.227.105 sensor
```

```

PT_Mid_temp | 32.000 | degrees C | ok | na | na | na | 78.000 |
80.000 | 85.000
NPU_Near_temp | 29.000 | degrees C | ok | na | na | na | na |
na | na
PT_Left_temp | 28.000 | degrees C | ok | na | na | na | na |
na | na
PT_Right_temp | 30.000 | degrees C | ok | na | na | na | na |
na | na
ILET_AF_temp | 26.000 | degrees C | ok | na | na | na | na |
na | na
PSU1_AF_temp | 24.000 | degrees C | ok | na | na | na | 61.000 |
64.000 | na
PSU2_AF_temp | 25.000 | degrees C | ok | na | na | na | na |
na | na
PSU1_temp | 33.000 | degrees C | ok | na | na | na | na |
na | na
PSU2_temp | na | degrees C | na | na | na | na | na |
na | na
CPU_temp | 31.000 | degrees C | ok | na | na | na | 90.000 |
94.000 | na
FAN1_Rear_rpm | 9120.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN2_Rear_rpm | 9000.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN3_Rear_rpm | 9000.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN4_Rear_rpm | 9000.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN1_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN2_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN3_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
FAN4_Front_rpm | 10080.000 | RPM | ok | na | 1080.000 | na | na |
na | na
PSU1_rpm | 9120.000 | RPM | ok | na | na | na | na |

```

na		na								
PSU2_rpm		na		RPM		na		na		na
na		na								
PSU_Total_watt		110.000		Watts		ok		na		na
na		na								
PSU1_stat		0x0		discrete		0x0180		na		na
na		na								
PSU2_stat		0x0		discrete		0x0380		na		na
na		na								
PSU1_In_watt		110.000		Watts		ok		na		na
na		na								
PSU1_In_volt		205.700		Volts		ok		na		na
na		na								
PSU1_In_amp		0.480		Amps		ok		na		na
na		na								
PSU1_Out_watt		90.000		Watts		ok		na		na
na		na								
PSU1_Out_volt		12.400		Volts		ok		na		na
na		na								
PSU1_Out_amp		7.500		Amps		ok		na		na
na		na								
PSU2_In_watt		na		Watts		na		na		na
na		na								
PSU2_In_volt		na		Volts		na		na		na
na		na								
PSU2_In_amp		na		Amps		na		na		na
na		na								
PSU2_Out_watt		na		Watts		na		na		na
na		na								
PSU2_Out_volt		na		Volts		na		na		na
na		na								
PSU2_Out_amp		na		Amps		na		na		na
na		na								
ACPI_stat		0x0		discrete		0x0180		na		na
na		na								
FAN1_prsnt		0x0		discrete		0x0180		na		na
na		na								
FAN2_prsnt		0x0		discrete		0x0180		na		na
na		na								
FAN3_prsnt		0x0		discrete		0x0180		na		na
na		na								
FAN4_prsnt		0x0		discrete		0x0180		na		na
na		na								
FAN1_Rear_stat		0x0		discrete		0x0080		na		na
na		na								
FAN2_Rear_stat		0x0		discrete		0x0080		na		na
na		na								
FAN3_Rear_stat		0x0		discrete		0x0080		na		na
na		na								
FAN4_Rear_stat		0x0		discrete		0x0080		na		na
na		na								
FAN1_Front_stat		0x0		discrete		0x0080		na		na
na		na								
FAN2_Front_stat		0x0		discrete		0x0080		na		na
na		na								
FAN3_Front_stat		0x0		discrete		0x0080		na		na
na		na								
FAN4_Front_stat		0x0		discrete		0x0080		na		na
na		na								
INTER_5.0V_volt		4.900		Volts		ok		4.200		4.500
5.500		5.700								
INTER_3.3V_volt		3.300		Volts		ok		2.800		3.000
3.600		3.800								
FPGA_1.0V_volt		0.990		Volts		ok		0.850		0.900
1.100		1.150								
FPGA_1.2V_volt		1.190		Volts		ok		1.020		1.080
1.320		1.380								
FPGA_1.8V_volt		1.780		Volts		ok		1.530		1.620
1.980		2.070								

FPGA_3.3V_volt	3.200	Volts	ok	2.800	3.000	3.100	3.500
3.600	3.800						
BMC_2.5V_volt	2.400	Volts	ok	2.100	2.200	2.300	2.600
2.800	2.900						
BMC_1.15V_volt	1.150	Volts	ok	0.980	1.030	1.090	1.210
1.270	1.320						
BMC_1.2V_volt	1.210	Volts	ok	1.020	1.080	1.140	1.260
1.320	1.380						
SWITCH_6.8V_volt	7.000	Volts	ok	5.800	6.100	6.400	7.200
7.500	7.800						
SWITCH_3.3V_volt	3.300	Volts	ok	2.800	3.000	3.100	3.500
3.600	3.800						
SWITCH_1.8V_volt	1.790	Volts	ok	1.530	1.620	1.710	1.890
1.980	2.070						
USB_5.0V_volt	4.900	Volts	ok	4.200	4.500	4.700	5.200
5.500	5.700						
NPU_1.2V_volt	1.190	Volts	ok	1.020	1.080	1.140	1.260
1.320	1.380						
NPU_VDDCORE_volt	0.800	Volts	ok	0.700	0.720	0.740	0.910
0.930	0.950						
NPU_VDDANLG_volt	0.790	Volts	ok	0.680	0.720	0.760	0.840
0.880	0.920						
BMC_boot	0x0	discrete	0x0180	na	na	na	na
na	na						
SEL_sensor	0x0	discrete	0x1080	na	na	na	na
na	na						

To access BMC over a LAN, use the following `ipmitool` command:

```
ipmitool [-c|-h|-v|-V] -I lanplus -H <hostname> [-p <port>]
```

```
[-U <username>]
[-L <privlvl>]
[-a|-E|-P|-f <password>]
[-o <oemtype>]
[-O <sel oem>]
[-C <ciphersuite>]
[-Y|[-K|- <kg_key>]
[-y <hex_kg_key>]
[-e <esc_char>]
[-N <sec>]
[-R <count>]
<command>
```

If needed, you can download `ipmitool` from the <https://sourceforge.net/projects/ipmitool> website. The commands to install `ipmitool` on Ubuntu or Fedora versions are as follows:

- 1 Install `ipmitool` on Ubuntu versions.


```
# apt-get install ipmitool
```
- 2 Install `ipmitool` on Fedora versions.


```
# yum install ipmitool
```

Run standard IPMI commands from `ipmitool`. For the command format, see *Intelligent Platform Management Interface Specification Second Generation v2.0.pdf*. For more documentation, see <https://linux.die.net/man/1/ipmitool>.

NOTE: Throughout this user guide, *Intelligent Platform Management Interface Specification Second Generation v2.0.pdf* is known as *IPMI Specification v2.0*. For more information about IPMI, see the IPMI resources that is hosted by Intel at <https://www.intel.com/content/www/us/en/servers/ipmi/ipmi-technical-resources.html>.

Topics:

- [Configurations](#)
- [Date and time](#)
- [SNMP and email alerts](#)
- [Add and delete users](#)
- [Firewall](#)

- Event log
- Default configuration Restore

Configurations

LAN configurations

For network settings, see the *IPMI Specification v2.0* chapter 23.1 *Set LAN Configuration Parameters Command* and Table 23-4 *LAN Configuration Parameters*.

In addition to setting IP addresses, use `ipmitool` to set the network mask, MAC address, default gateway IP and MAC addresses, and so forth.

`ipmitool` commands:

root@dellenc-diag-os:~# ipmitool lan set 1

```
usage: lan set <channel> <command> <parameter>
LAN set command/parameter options:
ipaddr <x.x.x.x>           Set channel IP address
netmask <x.x.x.x>         Set channel IP netmask
macaddr <x:x:x:x:x:x>     Set channel MAC address
defgw ipaddr <x.x.x.x>    Set default gateway IP address
defgw macaddr <x:x:x:x:x:x> Set default gateway MAC address bakgw
ipaddr <x.x.x.x>         Set backup gateway IP address
bakgw macaddr <x:x:x:x:x:x> Set backup gateway MAC address
password <password>     Set session password for this channel
snmp <community string> Set SNMP public community string
user                     Enable default user for this channel
access <on|off>         Enable or disable access to this channel
alert <on|off>         Enable or disable PEF alerting for this channel
arp respond <on|off>    Enable or disable BMC ARP responding
arp generate <on|off>   Enable or disable BMC gratuitous ARP generation
arp interval <seconds>  Set gratuitous ARP generation interval
vlan id <off|<id>>      Disable or enable VLAN and set ID (1-4094)
vlan priority <priority> Set vlan priority (0-7)
auth <level> <type,..> Set channel authentication types
    level = CALLBACK, USER, OPERATOR, ADMIN
    type  = NONE, MD2, MD5, PASSWORD, OEM
ipsrc <source>         Set IP Address source
    none  = unspecified source
    static = address manually configured to be static
    dhcp  = address obtained by BMC running DHCP
    bios  = address loaded by BIOS or system software
cipher_privs XXXXXXXXXXXXXXXX Set RMCP+ cipher suite privilege levels
X = Cipher Suite Unused
c = CALLBACK
u = USER
o = OPERATOR
a = ADMIN
O = OEM bad_pass_thresh <thresh_num> <l|0> <reset_interval> <lockout_interval>
    Set bad password threshold
```

NOTE: Dell EMC recommends setting LAN parameters from the host microprocessor. You can run all other `ipmitool` options from a remote machine after the BMC has the correct IP address and LAN settings. When running `ipmitool` from a remote machine, the command prefix is `ipmitool -H <ip address of BMC> -I lanplus -U <user_name> -P <password> ..."`

The `<channel>` number refers to the LAN channel, which is 1 in this BMC implementation.

Dell EMC recommends executing the LAN settings command from a system-side machine rather than from a remote machine. To set a dynamic host configuration protocol (DHCP) IP address, use the following command:

```
# ipmitool lan set 1 ipsrc dhcp
```

To set a static IP address:

```
# ipmitool lan set 1 ipsrc static
# ipmitool lan set 1 ipaddr <x.x.x.x>
```

You can also add the BMC IP address from the BIOS. For more information, see the BIOS manual at www.dell.com/support.

DNS configuration

Use these commands to set and get domain name server (DNS)-related settings, for example hostname, domain setting, and DNS server settings. BMC supports only three DNS server IP addresses. These IP addresses can be either IPv4 or IPv6.

To set DNS configuration details, use the DNS configuration command. The DNS configuration is buffered and applies only after you set a DNS Restart—parameter #7.

Date and time

BIOS sets the date and time during boot up. Use the `iselttime` tool that is part of the `ipmiutil` package. Use the `ipmiutil` command only on the local processor. For more information about the `ipmiutil` command, see [ipmiutil package](#).

Install the `ipmiutil` package and use the `iselttime` command.

To override the date and time used in the system event log (SEL) log, use the following command:

```
root@dellemc-diag-os:~# ipmitool sel time get
08/01/2018 15:10:46
root@dellemc-diag-os:~# ipmitool sel time set
usage: sel time set "mm/dd/yyyy hh:mm:ss"
root@dellemc-diag-os:~#
```

For `ipmiutil/iselttime`, download and install the binaries and documentation from <http://ipmiutil.sourceforge.net>. Also, various Linux distributions have binary packages prebuilt and available for download.

For Fedora, to download the utilities, use https://fedora.pkgs.org/26/fedora-x86_64/ipmiutil-3.0.1-2.fc26.x86_64.rpm.html.

SNMP and email alerts

Event filters

To set the platform event filters, use the `raw` command format. To configure an entry in the filter table:

```
root@dellemc-diag-os:~# ipmitool raw 0x04 0x12 0x6 0x2 0xc0 0x1 0x2 0x2 0xff 0xff 0xff 0xff 0x01 0x0 0x0 0x0 0x0 0x0 0x0
0x0 0x0 0x0 0x0
Byte 3 (0x60) - event filter table cmd
Byte 4 (0x2) - filter number
Byte 5 (0xc0) - filter config(enable)
Byte 6 (0x1) - action(alert)
Byte 7 (0x2) - policy number
Byte 8 (0x2) - event severity(information)
Byte 9 (0xff) - slave address
```

Byte 10 (0xff) - channel number (any)
Byte 11 (0xff) - sensor number (any)
Byte 12 (0x01) - event trigger (threshold)

The entry 2 is changed after the command, as shown:

```
root@dellemc-diag-os:~#  
root@dellemc-diag-os:~# ipmitool pef filter list  
1 | disabled, configurable  
2 | enabled, pre-configured | Any | Any | Information | OEM | Any | Alert | 2  
3 | disabled, configurable  
4 | disabled, configurable  
5 | disabled, configurable  
6 | disabled, configurable  
7 | disabled, configurable  
8 | disabled, configurable  
9 | disabled, configurable  
10 | disabled, configurable  
11 | disabled, configurable  
12 | disabled, configurable  
13 | disabled, configurable  
14 | disabled, configurable  
15 | disabled, configurable  
16 | disabled, configurable  
17 | disabled, configurable  
18 | disabled, configurable  
19 | disabled, configurable  
20 | disabled, configurable  
21 | disabled, configurable  
22 | disabled, configurable  
23 | disabled, configurable  
24 | disabled, configurable  
25 | disabled, configurable  
26 | disabled, configurable  
27 | disabled, configurable  
28 | disabled, configurable  
29 | disabled, configurable  
30 | disabled, configurable  
31 | disabled, configurable  
32 | disabled, configurable  
33 | disabled, configurable  
34 | disabled, configurable  
35 | disabled, configurable  
36 | disabled, configurable  
37 | disabled, configurable  
38 | disabled, configurable  
39 | disabled, configurable  
40 | disabled, configurable
```

For more information, see the *IPMI Specification v2.0* chapter 17.7 *Event Filter Table* and chapter 30.3 *Set PEF Configuration Parameters Command*.

Alert policies and destinations

For more information, see the *IPMI Specification v2.0* chapter 17.11 *Alert Policy Table* and chapter 30.3 *Set PEF Configuration Parameters Command (parameter 9)*.

LAN destinations

BMC supports SNMP alert destinations. These are SNMP traps. When you set a LAN destination for alerts, the BMC sends an SNMP trap to the set a destination whenever BMC detects alert conditions. You can setup the SNMP management application on the destination to receive these SNMP traps; however, setting up the SNMP management station is beyond the scope of this document.

To view alert destinations, use the `ipmitool lan alert print` command.

```
root@dellenc-diag-os:~# ipmitool lan alert print
Alert Destination      : 0
Alert Acknowledge     : Unacknowledged
Destination Type      : PET Trap
Retry Interval        : 0
Number of Retries     : 0
Alert Gateway         : Default
Alert IP Address      : 0.0.0.0
Alert MAC Address     : 00:00:00:00:00:00
Alert Destination     : 1
Alert Acknowledge     : Unacknowledged
Destination Type      : PET Trap
Retry Interval        : 0
Number of Retries     : 0
Alert Gateway         : Default
Alert IP Address      : 0.0.0.0
Alert MAC Address     : 00:00:00:00:00:00
Alert Destination     : 2
Alert Acknowledge     : Unacknowledged
Destination Type      : PET Trap
Retry Interval        : 0
Number of Retries     : 0
Alert Gateway         : Default
Alert IP Address      : 0.0.0.0
Alert MAC Address     : 00:00:00:00:00:00
.
.
.
Alert Destination     : 15
Alert Acknowledge     : Unacknowledged
Destination Type      : PET Trap
Retry Interval        : 0
Number of Retries     : 0
Alert Gateway         : Default
Alert IP Address      : 0.0.0.0
Alert MAC Address     : 00:00:00:00:00:00
```

You can configure up to 15 destinations. To configure destination 1 to send an alert to a machine with IP address 10.11.227.180:

```
root@dellenc-diag-os:~# ipmitool lan alert set 1 ipaddr 10.11.227.105
Setting LAN Alert 1 IP Address to 10.11.227.105
```

The following output using the `ipmitool lan alert print` command shows the configuration was successful:

```
root@dellenc-diag-os:~# ipmitool lan alert print 1
Alert Destination     : 1
Alert Acknowledge     : Unacknowledged
Destination Type      : PET Trap
Retry Interval        : 0
Number of Retries     : 0
Alert Gateway         : Default
Alert IP Address      : 10.11.227.105
Alert MAC Address     : 00:00:00:00:00:00
```

Alert policy setup

To setup the alert policy, you must use the `ipmitool raw` command.

To view the current policy table, use the `ipmitool pef policy list` command.

```
root@dellemc-diag-os:~# ipmitool pef policy list
1 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
2 | 2 | enabled | Match-always | 1 | 802.3 LAN | PET | AMI | 0 | 0 | 10.11.227.105 | 00:00:00:00:00:00
3 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
4 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
5 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
6 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
7 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
8 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
9 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
10 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
.
.
.
57 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
58 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
59 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
60 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
```

There are 60 entries available for a policy table. The following example shows setting a policy entry. For a detailed description of the table entries, see the *IPMI Specification v2.0 Alert policy table entry*.

```
root@dellemc-diag-os:~# ipmitool raw 0x4 0x12 0x9 0x2 0x28 0x11 0x00

root@dellemc-diag-os:~# ipmitool pef policy list
1 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
2 | 2 | enabled | Match-always | 1 | 802.3 LAN | PET | AMI | 0 | 0 | 10.11.227.105 | 00:00:00:00:00:00
3 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
4 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
5 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
6 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
7 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
8 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
9 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
10 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
.
.
.
57 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
58 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
59 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
60 | 0 | disabled | Match-always | 0 | IPMB (I2C) | 0
```

Add and delete users

The following describes adding and deleting users:

There are 10 entries for a user list.

- 1 Add a new user by modifying one of the empty entries in the user list using the following:

```
$. /ipmitool -H xx.xx.xxx.xx -I lanplus -U admin -P admin user set name 3 <name>
$. /ipmitool -H xx.xx.xxx.xx -I lanplus -U admin -P admin user set password 3
Password for user 3:
```



```
Password for user 3:  
Set User Password command successful (user 3)
```

Step 1 creates a user with no access.

- 2 Set the privilege level for the user in Step 1 using the following:

```
$/ipmitool -H xx.xx.xxx.xx -I lanplus -U admin -P admin user priv 3  
User Commands:  
summary      [<channel number>]  
list         [<channel number>]  
set name     <user id> <username>  
set password <user id> [<password> <16|20>]  
disable     <user id>  
enable      <user id>  
priv        <user id> <privilege level> [<channel number>]  
  Privilege levels:  
  * 0x1 - Callback  
  * 0x2 - User  
  * 0x3 - Operator  
  * 0x4 - Administrator  
  * 0x5 - OEM Proprietary  
  * 0xF - No Access  
  
test        <user id> <16|20> [<password>]
```

```
$/ipmitool -H xx.xx.xxx.xx -I lanplus -U admin -P admin user priv 3 2  
Set Privilege Level command successful (user 3)  
$/ipmitool -H xx.xx.xxx.xx -I lanplus -U admin -P admin user list  
ID Name      Callin Link Auth IPMI Msg Channel Priv Limit  
1      false  false  true   ADMINISTRATOR  
2  admin  true   true   true   ADMINISTRATOR  
3  <name> true   true   true   USER  
4      true   false  false  NO ACCESS  
5      true   false  false  NO ACCESS  
6      true   false  false  NO ACCESS  
7      true   false  false  NO ACCESS  
8      true   false  false  NO ACCESS  
9      true   false  false  NO ACCESS  
10     true   false  false  NO ACCESS
```

You can individually enable channels for a certain privilege level access. For example, to place the LAN channel accessible for "USER" level access, use the following:

```
$/ipmitool -H xx.xx.xxx.xxx -I lanplus -U admin -P admin channel setaccess 1 3 callin=off link=off ipmi=on privilege=1  
Set User Access (channel 1 id 3) successful.  
$/ipmitool -H xx.xx.xxx.xxx -I lanplus -L USER -U <name> -P <name> fru  
Get Device ID command failed: 0xd4 Insufficient privilege level  
FRU Device Description : Builtin FRU Device (ID 0)  
Get Device ID command failed: Insufficient privilege level  
$/ipmitool -H xx.xx.xxx.xxx -I lanplus -U admin -P admin channel setaccess 1 3 callin=off link=off ipmi=on privilege=2  
Set User Access (channel 1 id 3) successful.  
$/ipmitool -H xx.xx.xxx.xx -I lanplus -L USER -U <name> -P <name> fru  
FRU Device Description : Builtin FRU Device (ID 0)  
Board Mfg Date       : Mon Feb 12 08:00:00 2018  
Board Mfg            : Dell  
Board Product        : <platform>  
Board Serial         : CNCES0082C0002  
Board Part Number    : 0G1T60X01  
Product Manufacturer : Dell  
Product Name         : <platform>  
Product Version      : 00  
Product Serial       : X1  
Product Asset Tag    : D4SSG02  
  
FRU Device Description : FRU_PSU1 (ID 1)  
Unknown FRU header version 0x00
```

```
FRU Device Description : FRU_PSU2 (ID 2)
Board Mfg Date       : Fri Jan 12 18:47:00 2018
Board Mfg           : DELL
Board Product       : PWR_SPLY,495W,RDNT,DELTA
Board Serial        : CNDED0081G01GL
Board Part Number   : 0GRTNKA02
```

```
FRU Device Description : FRU_FAN1 (ID 3)
Unknown FRU header version 0x00
```

```
FRU Device Description : FRU_FAN2 (ID 4)
Board Mfg Date       : Mon Feb 12 08:01:00 2018
Board Mfg           : Dell
Board Product       : <platform>
Board Serial        : CNCES008260036
Board Part Number   : 07CRC9X01
Product Manufacturer : Dell
Product Name       : <platform>
Product Version    :
Product Serial     :
Product Asset Tag   : D4SSG02
```

For more information, see the *IPMI Specification v2.0* chapter 22.26 *Set User Access Command*, 22.28 *Set User Name Command*, and 22.30 *Set User Password Command*.

- Request data byte 1—[7]
 - 0b-Do not change the following bits in this byte
 - 1b-Enable changing bits in this byte
- Request data byte 1—[6] User restricted to callback
 - 0b-User Privilege Limit is determined by the User Privilege Limit parameter for both callback and non-callback connections.
 - 1b-User Privilege Limit is determined by the User Privilege Limit parameter for callback connections, but is restricted to Callback level for non-callback connections. A user can only initiate a callback when he/she 'calls in' to the BMC, but after the callback connect is made, the user could potentially establish a session as an Operator.
- Request data byte 1—[5] User link authentication enable/disable. This is used to enable/disable a user's name and password information for link authentication. Link authentication itself is a global setting for the channel and is enabled/disabled via the serial or modem configuration parameters.
 - 0b-disable user for link authentication
 - 1b-enable user for link authentication
- Request data byte 1—User IPMI Messaging enable/disable. This is used to enable/disable a user's name and password information for IPMI messaging. In this case, *IPMI Messaging* means the ability to execute generic IPMI commands that are not associated with a particular payload type. For example, if you disable IPMI Messaging for a user, but that user is enabled for activating the SOL payload type, IPMI commands associated with SOL and session management, such as *Get SOL Configuration parameters* and *Close Session* are available, but generic IPMI commands such as *Get SEL Time* are not.
 - 0b-disable user for link authentication
 - 1b-enable user for link authentication
- Request data byte 2—User ID
 - [7:6] reserved
 - [5:0] User ID. 00000b = reserved
- Request data byte 3—User limits
 - [7:6] reserved
 - [3:0] User Privilege Limit. This determines the maximum privilege level that the user can switch to on the specified channel.
 - 0h-reserved
 - 1h-Callback
 - 2h-User
 - 3h-Operator
 - 4h-Administrator

- 5h-OEM Proprietary
- Fh-NO ACCESS
- Request data byte (4)—User Session Limit. Optional—Sets how many simultaneous sessions are activated with the username associated with the user. If not supported, the username activates as many simultaneous sessions as the implementation supports. If an attempt is made to set a non-zero value, a CCh "invalid data field" error returns.
 - [7:4]-Reserved
 - [3:0]-User simultaneous session limit. 1=based. oh=only limited by the implementations support for simultaneous sessions.
- Response data byte 1—Completion code

① NOTE: If the user access level is set higher than the privilege limit for a given channel, the implementation does not return an error completion code. If required, it is up to the software to check the channel privilege limits set using the `Set Channel Access` command and provide notification of any mismatch.

Set User Name Command

- Request data byte 1—User ID
 - [7:6]-reserved
 - [5:0]-User ID. 000000b-reserved. User ID 1 is permanently associated with User 1, the null user name.
- Request data byte 2:17—User Name String in ASCII, 16 bytes maximum. Strings with fewer than 16 characters terminate with a null (00h) character. The 00h character is padded to 16 bytes. When the string is read back using the `Get User Name` command, those bytes return as 0s.
- Response data byte 1—Completion code

Set User Password Command

- Request data byte 1—User ID. For IPMI v20, the BMC supports 20-byte passwords (keys) for all user IDs that have configurable passwords. The BMC maintains an internal tag indicating if the password is set as a 16-byte or 20-byte password. Use a 16-byte password in algorithms that require a 20-byte password. The 16-byte password is padded with 0s to create 20-bytes.

If an attempt is made to test a password that is stored as a 20-byte password as a 16-byte password, and vice versa, the `test password` operation returns a `test failed` error completion code.

You cannot use a password stored as a 20-byte password to establish an IPMI v1.5 session. You must set the password as a 16-byte password to configure the same password for both IPMI v20 and IPMI v1.5 access. The password is padded with 0s as necessary.

Use the `test password` operation to determine if a password is stored as 16-bytes or 20-bytes.

- Request data byte 2—
 - [7:2] Reserved
 - [1:0] Operation
 - 00b-disable user
 - 01b-enable user-10b-set password
 - 11b-test password. This compares the password data give in the request with the presently stored password and returns an OK completion code if it matches. Otherwise, an error completion code returns.
- Request data byte 3:18—For 16-byte passwords. Password data. This is a fixed-length required field used for setting and testing password operations. If the user enters the password as an ASCII string, it must be null (00h) terminated 00h padded if the string is shorter than 16 bytes. This field is not needed for the `disable user` or `enable user` operation. If the field is present, the BMC ignores the data.
- Request data byte 3:22—For 20-byte passwords. This is a fixed-length required field used for setting and testing password operations. If the user enters the password as an ASCII string, it must be null (00h) terminated 00h padded if the string is shorter than 20 bytes. This field is not needed for the `disable user` or `enable user` operation. If the field is present, the BMC ignores the data.
- Response data byte 1—Completion code. Generic plus the following command-specific completion codes:
 - 80h-mandatory password test failed. Password size is correct but the password data does not match the stored value.

- 81h-mandatory password test failed. Wrong password size.

Firewall

To set a firewall, use the `set firewall configuration` command. Use parameters 0–3 to add the iptables rules and 4–7 to remove the iptables rules.

- NetFN—0x32
- Command—0x76
- Request data Byte 1—parameter selector
- Request data Byte 2—State selector
- Request data Byte 3:N—Configuration parameter data
- Response data Byte 1—Completion code
 - 80h—Parameter not supported
 - 81h—Invalid time (start/stop time)
 - 82h—Attempt to write read-only parameter
 - 83h—Attempt to access HTTP Port 80

To set the firewall configuration state, use the following:

Table 2. Firewall set parameters

Type specific param	#	Parameter data
To set the command to DROP	00	Parameter to drop packets. Parameter 0–3 uses this state to add the rules to drop the packets based on the IP address/port number or ange of IP addresses/port numbers. Use parameter 4–7 to remove the rule.
To set the command to ACCEPT	01	Parameter to accept packets. Parameter 0–3 uses this state to add the rules to accept the packets based on the IP address/port number or ange of IP addresses/port numbers. Use parameter 4–7 to remove the rule.

To set the firewall parameters, use the following:

Table 3. Firewall parameters

Parameter	#	Parameter data
Add the IPv4 address rule	0	Data 1:4—IP address MS-byte first. This is an IPv4 address that is blocked or unblocked based on the state.
Add the range of IPv4 addresses rule	1	Data 1:8—IP address range [1:4]—Starting IP address from which IPs are blocked or unblocked based on the state.

Parameter	#	Parameter data
		<p>[5:8]—Ending IP address until IPs are blocked or unblocked based on the state.</p> <p>For example, if the IP address is x1.x2.x3.x4, the format is:</p> <p>1st byte = x1</p> <p>2nd byte = x2</p> <p>3rd byte = x3</p> <p>4th byte = x4</p>
Add the IPv4 port number rule	2	<p>Data 1:—Protocol TCP/UDP</p> <p>0 = TCP</p> <p>1 = UDP</p> <p>2 = both TCP and UDP</p> <p>Data 2:3—port number</p> <p>[2:3]—MX byte first. Port number blocked or unblocked based on the state.</p>
Add the Pv4 port number range rule	3	<p>Data 1:—Protocol TCP/UDP</p> <p>0 = TCP</p> <p>1 = UDP</p> <p>2 = both TCP and UDP</p> <p>Data 2:5—port range</p> <p>[2:3]—Port number from the ports blocked or unblocked based on the state.</p> <p>[4:5]—Port number till ports are blocked or unblocked based on the state.</p>
Remove the IPv4 address rule	4	<p>Data 1:4—IP address</p> <p>MS-byte first. This is the IPv4 address type that is blocked or unblocked based on state.</p>
Remove the range of IPv4 addresses rule	5	<p>Data 1:8—IP address range</p> <p>[1:4]—Starting IP address that is blocked or unblocked based on the state.</p> <p>[5:8]—Ending IP address that is blocked or unblocked based on the state.</p> <p>For example, if the IP address is x1.x2.x3.x4, the format is:</p> <p>1st byte = x1</p> <p>2nd byte = x2</p> <p>3rd byte = x3</p>

Parameter	#	Parameter data
Remove the IPv4 port number rule	6	<p>4th byte = x4</p> <p>Data 1:—Protocol TCP/UDP 0 = TCP 1 = UDP 2 = both TCP and UDP</p> <p>Data 2:3—port number [2:3]—Port number from the ports blocked or unblocked based on the state.</p>
Remove the IPv4 port range rule	7	<p>Data 1:—Protocol TCP and UDP 0 = TCP 1 = UDP 2 = both TCP and UDP</p> <p>Data 2:5—port range [2:3]—Port number from the ports blocked or unblocked based on the state. [4:5]—Port number till ports are blocked or unblocked based on the state.</p>
Flush IPv4 and IPv6 iptable	8	Flush all the rules set using iptables and ip6tables.
Drop all	9	<p>Add iptables rules to block IPv4 and IPv6 traffic to the BMC. The state selector is not used.</p> <p>Data1: Protocol Bit 7:2—Reserved Bit 1—IPv6 Bit 0—IPv4</p>
Remove drop all rule	10	<p>Remove iptables rules to block IPv4 and IPv6 traffic to the BMC. The state selector is not used.</p> <p>Data1: Protocol Bit 7:2—Reserved Bit 1—IPv6 Bit 0—IPv4</p>
Add IPv4 address with timeout rule	11	<p>Data 1:4—IP address MS-byte first. The IPv4 address type blocked or unblocked based on the state.</p>

Parameter	#	Parameter data
Add IPv4 range of addresses with timeout rule	12	<p>Date 5:10—Start time</p> <p>[5:6]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>7—month</p> <p>8—date</p> <p>9—hour</p> <p>10—minute</p> <p>Date 11-16—stop time</p> <p>[11:12]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>13—month</p> <p>14—date</p> <p>15—hour</p> <p>16—minute</p>
Add the IPv4 port number with timeout rule	13	<p>Data 1:8—IP address</p> <p>[1:4]—Starting IP address blocked or unblocked based on the state.</p> <p>[5:8]—Ending IP address till IPs are blocked or unblocked based on the state.</p> <p>Date 9:14—Start time</p> <p>[9:10]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>11—month</p> <p>12—date</p> <p>13—hour</p> <p>14—minute</p> <p>Date 15-20—Stop time</p> <p>[15:16]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>Data 1—Protocol TCP and UDP</p> <p>0 = TCP</p>

Parameter	#	Parameter data
		1 = UDP
		2 = both TCP and UDP
		Data 2:3—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
		Date 4:9—Start time
		[4:5]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		6—month
		7—date
		8—hour
		9—minute
		Date 10-15—stop time
		[10:11]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		12—month
		13—date
		14—hour
		15—minute
Add the IPv4 port range with timeout rule	14	Data 1:—Protocol TCP and UPD
		0 = TCP
		1 = UDP
		2 = both TCP and UDP
		Data 2:5—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
		[4:5]—Port number till the ports blocked or unblocked based on the state.
		Date 6:11Start time
		[6:7]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		8—month

Parameter	#	Parameter data
		9—date
		10—hour
		11—minute
		Date 12-17—stop time
		[12:13]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		14—month
		15—date
		16—hour
		17—minute
Remove the IPv4 address with timeout rule	15	Data 1:4—IP address
		MS-byte first. The IPv4 address type blocked or unblocked based on the state.
		Date 5:10—Start time
		[5:6]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		7—month
		8—date
		9—hour
		10—minute
		Date 11-16—stop time
		[11:12]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		13—month
		14—date
		15—hour
		16—minute
Remove the range IPv4 address with timeout rule	16	Data 1:8—IP address
		[1:4]—Starting IP address blocked or unblocked based on the state.
		[5:8]—Ending IP address till IPs are blocked or unblocked based on the state.

Parameter	#	Parameter data
Remove the IPv4 port number with timeout rule		Date 9:14—Start time
		[9:10]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		11—month
		12—date
		13—hour
		14—minute
		Date 15-20—Stop time
		[15:16]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		17—month
		18—date
		19—hour
		20—minute
		Data 1—Protocol TCP and UDP
		0 = TCP
		1 = UDP
		2 = both TCP and UDP
		Data 2:3—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
	Date 4:9—Start time	
	[4:5]—Year	
	LS-byte first if little endian system. Two-byte data required to form year.	
	6—month	
	7—date	
	8—hour	
	9—minute	
	Date 10-15—stop time	
	[10:11]—Year	

Parameter	#	Parameter data
		LS-byte first if little endian system. Two-byte data required to form year.
		12—month
		13—date
		14—hour
		15—minute
Remove the IPv4 port number range with timeout rule	18	Data 1:—Protocol TCP and UDP 0 = TCP 1 = UDP 2 = both TCP and UDP Data 2:5—port number [2:3]—Port number from the ports blocked or unblocked based on the state. [4:5]—Port number till the ports blocked or unblocked based on the state. Date 6:11Start time [6:7]—Year LS-byte first if little endian system. Two-byte data required to form year. 8—month 9—date 10—hour 11—minute Date 12-17—stop time [12:13]—Year LS-byte first if little endian system. Two-byte data required to form year. 14—month 15—date 16—hour 17—minute
Drop all IPv4 or IPv6 with timeout rule	19	Add iptables rules to block IPv4 and IPv6 traffic to the BMC. The state selector is not used. Data1: Protocol

Parameter	#	Parameter data
Remove drop all Ipv4 or IPv6 with timeout rule	20	<p>Bit 7:2—Reserved</p> <p>Bit 1—IPv6</p> <p>Bit 0—IPv4</p> <p>Date 2:7—Start time</p> <p>[2:3]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>4—month</p> <p>5—date</p> <p>6—hour</p> <p>7—minute</p> <p>Date 8:13—Stop time</p> <p>[8:9]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>10—month</p> <p>11—date</p> <p>12—hour</p> <p>13—minute</p> <p>Add iptables rules to block IPv4 and IPv6 traffic to the BMC. The state selector is not used.</p> <p>Data1: Protocol</p> <p>Bit 7:2—Reserved</p> <p>Bit 1—IPv6</p> <p>Bit 0—IPv4</p> <p>Date 2:7—Start time</p> <p>[2:3]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>4—month</p> <p>5—date</p> <p>6—hour</p> <p>7—minute</p>

Parameter	#	Parameter data
		<p>Date 8:13—Stop time</p> <p>[8:9]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>10—month</p> <p>11—date</p> <p>12—hour</p> <p>13—minute</p>
Add IPv6 address with timeout rule	21	<p>Data 1:16—IPv6 address</p> <p>MS-byte first. The IPv6 address type blocked or unblocked based on the state.</p> <p>Date 7:22—Start time</p> <p>[17:18]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>19—month</p> <p>20—date</p> <p>21—hour</p> <p>22—minute</p> <p>Date 23-28—stop time</p> <p>[23:24]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>25—month</p> <p>26—date</p> <p>27—hour</p> <p>28—minute</p>
Add IPv6 address range with timeout rule	22	<p>Data 1:16—IPv6 address range</p> <p>[1:16]—Port number from the ports blocked or unblocked based on the state.</p> <p>[17:32]—Port number till the ports blocked or unblocked based on the state.</p> <p>Date 33:38—Start time</p> <p>[33:34]—Year</p>

Parameter	#	Parameter data
		<p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>35—month</p> <p>36—date</p> <p>37—hour</p> <p>38—minute</p> <p>Date 39:44—stop time</p> <p>[39:40]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>41—month</p> <p>42—date</p> <p>43—hour</p> <p>44—minute</p>
Remove the IPv6 address with timeout rule	23	<p>Data 1:16—IPv6 address</p> <p>MS-byte first. The IPv4 address type blocked or unblocked based on the state.</p> <p>Date 17:22—Start time</p> <p>[17:18]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>19—month</p> <p>20—date</p> <p>21—hour</p> <p>22—minute</p> <p>Date 23-28—stop time</p> <p>[23:24]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>25—month</p> <p>26—date</p> <p>27—hour</p> <p>28—minute</p>
Remove the Ipv6 address range with timeout rule	24	Data 1:16—IPv6 address range

Parameter

#

Parameter data

Add the IPv6 port number with timeout rule 25

[1:16]—Port number from the ports blocked or unblocked based on the state.

[17:32]—Port number till the ports blocked or unblocked based on the state.

Date 33:38—Start time

[33:34]—Year

LS-byte first if little endian system. Two-byte data required to form year.

35—month

36—date

37—hour

38—minute

Date 39:44—stop time

[39:40]—Year

LS-byte first if little endian system. Two-byte data required to form year.

41—month

42—date

43—hour

44—minute

Data 1—Protocol TCP and UDP

0 = TCP

1 = UDP

2 = both TCP and UDP

Data 2:3—port number

[2:3]—Port number from the ports blocked or unblocked based on the state.

Date 4:9—Start time

[4:5]—Year

LS-byte first if little endian system. Two-byte data required to form year.

6—month

7—date

8—hour

9—minute

Parameter	#	Parameter data
Add the IPv6 port number range with timeout rule	26	<p>Date 10-15—stop time</p> <p>[10:11]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>12—month</p> <p>13—date</p> <p>14—hour</p> <p>15—minute</p> <p>Data 1—Protocol TCP and UDP</p> <p>0 = TCP</p> <p>1 = UDP</p> <p>2 = both TCP and UDP</p> <p>Data 2:5—port number</p> <p>[2:3]—Port number from the ports blocked or unblocked based on the state.</p> <p>[4:5]—Year</p> <p>Date 6:11—Start time</p> <p>[6:7]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>8—month</p> <p>9—date</p> <p>10—hour</p> <p>11—minute</p> <p>Date 12-17—stop time</p> <p>[12:13]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>14—month</p> <p>15—date</p> <p>16—hour</p> <p>17—minute</p>
Remove the IPv6 port number with timeout rule	27	<p>Data 1—Protocol TCP and UDP</p> <p>0 = TCP</p>

Parameter	#	Parameter data
Remove the IPv6 port range with timeout rule	28	<p>1 = UDP</p> <p>2 = both TCP and UDP</p> <p>Data 2:3—port number</p> <p>[2:3]—Port number from the ports blocked or unblocked based on the state.</p> <p>[4:9]—Year</p> <p>Date 4:9—Start time</p> <p>[4:5]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>6—month</p> <p>7—date</p> <p>8—hour</p> <p>9—minute</p> <p>Date 10-15—stop time</p> <p>[10:11]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p> <p>12—month</p> <p>12—date</p> <p>14—hour</p> <p>15—minute</p> <p>Data 1—Protocol TCP and UDP</p> <p>0 = TCP</p> <p>1 = UDP</p> <p>2 = both TCP and UDP</p> <p>Data 2:5—port number</p> <p>[2:3]—Port number from the ports blocked or unblocked based on the state.</p> <p>[4:5]—Year</p> <p>Date 6:11—Start time</p> <p>[6:7]—Year</p> <p>LS-byte first if little endian system. Two-byte data required to form year.</p>

Parameter	#	Parameter data
		8—month
		9—date
		10—hour
		11—minute
		Date 12-17—stop time
		[12:13]—Year
		LS-byte first if little endian system. Two-byte data required to form year.
		14—month
		15—date
		16—hour
		17—minute
Add the IPv6 address rule	29	Data 1:16—IPv6 address MS-byte first. This is an IPv6 address that is blocked or unblocked based on state.
Add the IPv6 address range rule	30	Data 1:16—IPv6 address range [1:16]—Starting IP address from which IPs are blocked or unblocked based on the state. [17:32]—Ending IP address until IPs are blocked or unblocked based on the state.
Remove the IPv6 address rule	31	Data 1:16—IPv6 address MS-byte first. This is an IPv6 address that is blocked or unblocked based on state.
Remove the IPv6 address range rule	32	Data 1:16—IPv6 address range [1:16]—Starting IP address from which IPs are blocked or unblocked based on the state. [17:32]—Ending IP address until IPs are blocked or unblocked based on the state.
Add the IPv6 port number rule	33	Data 1—Protocol TCP and UDP 0 = TCP 1 = UDP 2 = both TCP and UDP Data 2:3—port number [2:3]—Port number from the ports blocked or unblocked based on the state.
Add the IPv6 port number range rule	34	Data 1—Protocol TCP and UDP

Parameter	#	Parameter data
		0 = TCP
		1 = UDP
		2 = both TCP and UDP
		Data 2:5—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
		[4:5]—Port number till the ports are blocked or unblocked based on the state.
Remove the IPv6 port number rule	35	Data 1—Protocol TCP and UDP
		0 = TCP
		1 = UDP
		2 = both TCP and UDP
		Data 2:3—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
Remove the IPv6 port number range rule	36	Data 1—Protocol TCP and UDP
		0 = TCP
		1 = UDP
		2 = both TCP and UDP
		Data 2:5—port number
		[2:3]—Port number from the ports blocked or unblocked based on the state.
		[4:5]—Port number till the ports are blocked or unblocked based on the state.

Event log

To get the IPMI event log, use the `ipmitool sel list` command.

To clear the event log, use the `ipmitool sel clear` command.

For IPMI event log settings, see the *IPMI Specification v2.0* chapter 31.4 *Reserve SEL Command* and 31.5 *Get SEL Entry Command*.


Reserve system event log (SEL) command

Use reserve SEL to set the present owner of the SEL. This reservation provides a limited amount of protection on repository access from the IPMB when you delete or incrementally read records. Use get SEL to read the SEL repository.

- Response data byte 1—Completion code
 - 81h—cannot execute the command, SEL erase in progress

- Response data byte 2—Reservation ID, LS byte 0000h reserved.
- Response data byte 3—Reservation ID, SM byte

Get SEL command

- Request data byte 1:2—Reservation IS, LS byte first. Only required for a partial get. Otherwise use 0000h.
- Request data byte 3:4—SEL record ID, LS byte first.
 - 0000h=GET FIRST ENTRY
 - FFFFh=GET LAST ENTRY
- Request data byte 5—Offset into record
- Request data byte 6—Bytes to read. FFh means read entire record.
- Response data byte 1—Completion code. Returns an error completion code if the SEL is empty.
 - 81h=cannot execute the command, SEL erase in progress.
- Response data byte 2:3—Next SEL record ID. LS byte first (returns FFFFh if the record just returned is the last record).
 -  **NOTE: FFFFh is not allowed as the record ID of an actual record. For example, the record ID in Record Data for the last record cannot be FFFFh.**
- Response data byte 4:N—Record data, 16 bytes for the entire record.

Set LOG configuration command

To set the system or audit log configuration, use the `set LOG configuration` command.

- Netfn—0x32
- Command—0x68

Audit log configuration

- Request data byte 1—Cmd
 - [7:2] Reserved
 - [1:0] 01h—Audit log
- Request data byte 1—Status
 - [7:2] Reserved
 - [1:0] 01h—Disabled
 - 01h—Enable local
- Response data byte 1—00h=success
 - CCh=invalid data field
 - FFh=unspecified error
- Response data byte 1—Cmd
 - [7:2] Reserved
 - [1:0] 00h—system log
- Response data byte 2—Status
 - [7:2] Reserved
 - [1:0] 01h—Disabled
 - 01h—Enable local
- Response data byte 3-70 for REMOTE (68 bytes) or 3-7 for LOCAL (5 bytes)—ENABLED REMOTE

- **NOTE:** These request data bytes are required only when you enable either the local or remote system log.

```
64bytes : Hostname (ASCII)
Remote syslog server
4bytes : port number
```

To set the remote server ip address to 10.0.124.22 and port to 770:

```
ipmitool -I lanplus -H xx.xx.xx.xx -U xxx -P xxx raw 0x32 0x68 0x00
0x02 0x31 0x30 0x2e 0x30 0x2e 0x31 0x32 0x34 0x2e 0x32 0x32 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00
0x02 0x03 0x00 0x00
ENABLED LOCAL
4bytes : Size (LSB first)
size of each file to rotate (file size is from 3 to 65535 KB)
1bytes : Rotate
Number of back-up files after logrotate (maximum 1 file)
```

To set the file size to 100 bytes, use the IPMI command:

```
ipmitool -I lanplus -H xx.xx.xx.xx -U xxx -P xxx raw 0x32 0x68 0x00
0x01 0x64 0x00 0x00 0x00 0x01
```

Default configuration Restore

Use configuration restore to start the configuration from scratch. For example, use configuration restore to remove the old configuration and start over if you reinstall the system or move the system to a new location.

Restore default configuration command

- NetFn—0x32
- Command—0x66
- Response byte 1—Completion code

Set backup configuration flag

To set the backup flags for the `manage BMC configuration` command, use the `set backup configuration flag` command.

- NetFN—0x32
- Command—0xF3
- Request data byte 1:2—Byte 1 is the value specifies to back up a configuration feature or not.
 - [7]—Reserved
 - [6]—1b: Backup SNMP. 0b: Do not backup the simple network management protocol (SNMP)
 - [5]—1b: Backup SYSLOG. 0b: Do not backup SYSLOG
 - [4]—1b: Backup KVM. 0b: Do not backup keyboard, video, and mouse (KVM)
 - [3]—1b: Backup NTP. 0b: Do not backup network time protocol (NTP)
 - [2]—1b: Backup IPMI. 0b: Do not backup IPMI
 - [1]—1b: Backup NETWORK And SERVICES. 0b: Do not backup NETWORK And SERVICES
 - [0]—1b: Backup AUTHENTICATION. 0b: Do not backup AUTHENTICATION

- NOTE:** Reserved bits may be updated further based on the requirement.

- Response data byte 1—Completion code
 - 0x83—Authentication feature is not enabled
 - 0x84—NTP feature is not enabled
 - 0x85—KVM feature is not enabled
 - 0x86—SNMP feature is not enabled

Firmware update

To update the firmware from a remote machine, use the BMC LAN interface.

You can also update the firmware in the local host OS using the USB interface. The USB interface is between the BMC and the microprocessor. When using the USB, the BMC simulates a virtual USB device, then Yafuflash sends the image to the BMC via the USB bus. Typically the update process completes in five minutes.

For more information about Yafuflash, see the *S5200-ON Series Release Notes*.

Table 4. Firmware update

Tool	Medium	OS	Comments
Yafuflash	USB	Linux	Recommended—Host OS only
Yafuflash	LAN	Windows/Linux	Internal use only

The BMC virtual USB is disabled by default. Enable the USB before you update the firmware.

Update BMC by USB interface

Enable BMC virtual USB:

```
ipmitool raw 0x32 0xaa 0x00 (Then wait 15s)
```

Update Main BMC:

```
./Yafuflash -cd -mse 1 rom.ima
```

Update BMC by LAN interface

- 1 Ensure that the client Linux or Windows machine can ping the BMC IP address.
- 2 Open a command window.
- 3 Update the main BMC using the following command:

```
./Yafuflash -nw -ip bmc_ip -u admin -p admin -mse 1 bmc.ima
```

Host power control

The following are host power control commands:

- `Power Off`—the `ipmitool` powers off
- `Power On`—the `ipmitool` powers on
- `Power Cycle`—the `ipmitool` power cycles
- `Hard Reset`—the `ipmitool` power resets

Access system health sensors

To check sensor information, use the following command:

```
root@dell EMC-diag-os:~# ipmitool sensor list
```

To change the sensor threshold, see the *IPMI Specification v2.0* chapter 35.8 *Set Sensor Thresholds Command*.

- Request data byte 1—Sensor number, FFH=reserved
- Request data byte 2—
 - [7:6] - reserved. Write as 00b
 - [5] - 1b=set upper non-recoverable threshold
 - [4] - 1b=set upper critical threshold
 - [3] - 1b=set upper non-critical threshold
 - [2] - 1b=set lower non-recoverable threshold
 - [1] - 1b=set lower critical threshold
 - [0] - 1b=set lower non-critical threshold
- Request data byte 3—lower non-critical threshold. Ignored if bit 0 of byte 2 = 0
- Request data byte 4—lower critical threshold. Ignored if bit 1 of byte 2 = 0
- Request data byte 5—lower non-recoverable threshold. Ignored if bit 2 of byte 2 = 0
- Request data byte 6—upper non-critical threshold. Ignored if bit 3 of byte 2 = 0
- Request data byte 7—upper critical threshold value. Ignored if bit 4 of byte 2 = 0
- Request data byte 8—upper non-recoverable threshold value. Ignored if bit 5 of byte 2 = 0
- Response data byte 1—Completion code

ipmitool sensors

```
root@dell EMC-diag-os:~# ipmitool sensor list
```

```
PT_Mid_temp      | 32.000      | degrees C | ok   | na   | na   | na   | 78.000 | 80.000 |
85.000
NPU_Near_temp   | 29.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
PT_Left_temp    | 28.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
PT_Right_temp   | 30.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
ILET_AF_temp    | 26.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
PSU1_AF_temp    | 24.000      | degrees C | ok   | na   | na   | na   | 61.000 | 64.000 |
na
PSU2_AF_temp    | 25.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
PSU1_temp       | 33.000      | degrees C | ok   | na   | na   | na   | na     | na     |
na
PSU2_temp       | na          | degrees C | na   | na   | na   | na   | na     | na     |
na
CPU_temp        | 31.000      | degrees C | ok   | na   | na   | na   | 90.000 | 94.000 |
na
FAN1_Rear_rpm   | 9120.000    | RPM       | ok   | na   | 1080.000 | na   | na     | na     |
na
FAN2_Rear_rpm   | 9000.000    | RPM       | ok   | na   | 1080.000 | na   | na     | na     |
na
```

FAN3_Rear_rpm	9000.000	RPM	ok	na	1080.000	na	na	na	
na									
FAN4_Rear_rpm	9000.000	RPM	ok	na	1080.000	na	na	na	
na									
FAN1_Front_rpm	10080.000	RPM	ok	na	1080.000	na	na	na	
na									
FAN2_Front_rpm	10080.000	RPM	ok	na	1080.000	na	na	na	
na									
FAN3_Front_rpm	10080.000	RPM	ok	na	1080.000	na	na	na	
na									
FAN4_Front_rpm	10080.000	RPM	ok	na	1080.000	na	na	na	
na									
PSU1_rpm	9000.000	RPM	ok	na	na	na	na	na	
na									
PSU2_rpm	na	RPM	na	na	na	na	na	na	
na									
PSU_Total_watt	110.000	Watts	ok	na	na	na	na	na	
na									
PSU1_stat	0x0	discrete	0x0180	na	na	na	na	na	
na									
PSU2_stat	0x0	discrete	0x0380	na	na	na	na	na	
na									
PSU1_In_watt	110.000	Watts	ok	na	na	na	na	na	
na									
PSU1_In_volt	205.700	Volts	ok	na	na	na	na	na	
na									
PSU1_In_amp	0.480	Amps	ok	na	na	na	na	na	
na									
PSU1_Out_watt	90.000	Watts	ok	na	na	na	na	na	
na									
PSU1_Out_volt	12.400	Volts	ok	na	na	na	na	na	
na									
PSU1_Out_amp	7.500	Amps	ok	na	na	na	na	na	
na									
PSU2_In_watt	na	Watts	na	na	na	na	na	na	
na									
PSU2_In_volt	na	Volts	na	na	na	na	na	na	
na									
PSU2_In_amp	na	Amps	na	na	na	na	na	na	
na									
PSU2_Out_watt	na	Watts	na	na	na	na	na	na	
na									
PSU2_Out_volt	na	Volts	na	na	na	na	na	na	
na									
PSU2_Out_amp	na	Amps	na	na	na	na	na	na	
na									
ACPI_stat	0x0	discrete	0x0180	na	na	na	na	na	
na									
FAN1_prsnt	0x0	discrete	0x0180	na	na	na	na	na	
na									
FAN2_prsnt	0x0	discrete	0x0180	na	na	na	na	na	
na									
FAN3_prsnt	0x0	discrete	0x0180	na	na	na	na	na	
na									
FAN4_prsnt	0x0	discrete	0x0180	na	na	na	na	na	
na									
FAN1_Rear_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN2_Rear_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN3_Rear_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN4_Rear_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN1_Front_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN2_Front_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
FAN3_Front_stat	0x0	discrete	0x0080	na	na	na	na	na	

na									
FAN4_Front_stat	0x0	discrete	0x0080	na	na	na	na	na	
na									
INTER_5.0V_volt	4.900	Volts	ok	4.200	4.500	4.700	5.200	5.500	
5.700									
INTER_3.3V_volt	3.300	Volts	ok	2.800	3.000	3.100	3.500	3.600	
3.800									
FPGA_1.0V_volt	0.990	Volts	ok	0.850	0.900	0.950	1.050	1.100	
1.150									
FPGA_1.2V_volt	1.190	Volts	ok	1.020	1.080	1.140	1.260	1.320	
1.380									
FPGA_1.8V_volt	1.780	Volts	ok	1.530	1.620	1.710	1.890	1.980	
2.070									
FPGA_3.3V_volt	3.200	Volts	ok	2.800	3.000	3.100	3.500	3.600	
3.800									
BMC_2.5V_volt	2.400	Volts	ok	2.100	2.200	2.300	2.600	2.800	
2.900									
BMC_1.15V_volt	1.150	Volts	ok	0.980	1.030	1.090	1.210	1.270	
1.320									
BMC_1.2V_volt	1.210	Volts	ok	1.020	1.080	1.140	1.260	1.320	
1.380									
SWITCH_6.8V_volt	7.000	Volts	ok	5.800	6.100	6.400	7.200	7.500	
7.800									
SWITCH_3.3V_volt	3.300	Volts	ok	2.800	3.000	3.100	3.500	3.600	
3.800									
SWITCH_1.8V_volt	1.790	Volts	ok	1.530	1.620	1.710	1.890	1.980	
2.070									
USB_5.0V_volt	4.900	Volts	ok	4.200	4.500	4.700	5.200	5.500	
5.700									
NPU_1.2V_volt	1.190	Volts	ok	1.020	1.080	1.140	1.260	1.320	
1.380									
NPU_VDDCORE_volt	0.800	Volts	ok	0.700	0.720	0.740	0.910	0.930	
0.950									
NPU_VDDANLG_volt	0.790	Volts	ok	0.680	0.720	0.760	0.840	0.880	
0.920									
BMC_boot	0x0	discrete	0x0180	na	na	na	na	na	
na									
SEL_sensor	0x0	discrete	0x1080	na	na	na	na	na	
na									

Access FRU data

To check field replacement unit (FRU) data, use the following command:

```
root@dellemc-diag-os:~# ipmitool fru print
```

For more FRU information, see the *IPMI Specification v2.0* chapter 34.2 *Read FRU Data Command*.

- Request data 1—FRU device ID. FFh=reserved
- Request data 2—FRU inventory offset to read, LS byte
- Request data 3—FRU inventory offset to read, LS byte
 - Offset is in bytes or words-per-device. Access type returned in the `Get FRU Inventory Area Info` command output.
- Request data 4—Count to read. Count is '1' based.
- Response data 1—Completion code. Generic, plus the command specifics:
 - 81h=FRU device busy. The requested cannot be completed because the logical FRU device is in a state where FRU information is temporarily unavailable. This state is possibly due to a loss of arbitration if the FRU implements as a device on a shared bus.
 - Software can elect to retry the operation after a minimum of 30 milliseconds if the code returns. Dell EMC recommends that the management controllers incorporate built-in retry mechanisms. Generic IPMI does not take advantage of this completion code.
- Response data 2—Count returned. Count is '1' based.
- Response data 3:2=N—Requested data

ipmitool FRUs

```
root@dellemc-diag-os:~# ipmitool fru print
```

```
FRU Device Description : Builtin FRU Device (ID 0)
Board Mfg Date       : Sat May 19 06:04:00 2018
Board Mfg           : CES00
Board Product       : <platform>
Board Serial        : CN01XR4WCES0085F0002
Board Part Number   : 01XR4WX01
Product Manufacturer : CES00
Product Name        : <platform>
Product Asset Tag   : GDNRG02
FRU Device Description : PSU1_fru (ID 1)
Board Mfg Date       : Fri Mar 30 21:30:00 2018
Board Mfg           : DELL
Board Product       : PWR SPLY,750W,AC,PS/IO,DELTA
Board Serial        : CNDED0083U00D5
Board Part Number   : 0HXWNFA00FRU
Device Description  : PSU2_fru (ID 2)
Board Mfg Date       : Fri Mar 30 22:12:00 2018
Board Mfg           : DELL
Board Product       : PWR SPLY,750W,AC,PS/IO,DELTA
Board Serial        : CNDED0083U00BY
Board Part Number   : 0HXWNFA00FRU
Device Description  : FAN1_fru (ID 3)
Board Mfg Date       : Mon Jan 1 00:00:00 1996
Board Serial        : CN07R5RFCEs0084N0081
Board Part Number   : 07R5RFX01FRU
Device Description  : FAN2_fru (ID 4)
Board Mfg Date       : Mon Jan 1 00:00:00 1996
Board Serial        : CN07R5RFCEs0084N0080
Board Part Number   : 07R5RFX01FRU
Device Description  : FAN3_fru (ID 5)
```

Board Mfg Date : Mon Jan 1 00:00:00 1996
Board Serial : CN07R5RFCE0084N0083
Board Part Number : 07R5RFX01FRU
Device Description : FAN4_fru (ID 6)
Board Mfg Date : Mon Jan 1 00:00:00 1996
Board Serial : CN07R5RFCE0084N0082
Board Part Number : 07R5RFX01

ipmiutil package

NOTE: All commands are subject to change as the `ipmiutil` package evolves over time. For more information about the IPMI utility, use cases, and the newest list of subcommands, see the IPMI website that is hosted by Intel at <https://www.intel.com/content/www/us/en/servers/ipmi/ipmi-technical-resources.html>.

- `ipmiutil`—a metacommand to invoke each of the following functions:
 - `ipmiutil alarms (ialarms)`—show and set the front panel alarms, including light emitting diodes (LEDs) and relays.
 - `ipmiutil config (iconfig)`—list, save, or restore the BMC configuration parameters.
 - `ipmiutil cmd (icmd)`—send specific IPMI commands to the BMC for testing and debug purposes.
 - `ipmiutil discover (idiscover)`—discover the available IPMI LAN nodes on a subnet.
 - `ipmiutil events (ievents)`—a stand-alone utility to decode IPMI events and platform event trap (PET) data.
 - `ipmiutil firewall (ifirewall)`—discover the available IPMI LAN nodes on a subnet.
 - `ipmiutil fru (ifru)`—show decoded field replaceable units (FRU) board/product inventory data and write FRU asset tags.
 - `ifruset`—show decoded FRU inventory data and set a FRU product area.
 - `iselttime`—show and set the IPMI system event log (SEL) time according to the system time.
 - `ipmiutil fwum (ifwum)`—OEM firmware update manager extensions
 - `ipmiutil getevt (igetevent)`—receive any IPMI events and display them.
 - `ipmiutil health (ihealth)`—check and report the basic health of the IPMI BMC.
 - `ipmiutil hpm (ihpm)`—hardware platform management (HPM) firmware update manager extensions
 - `ipmiutil lan (ilan)`—show and configure the local area network (LAN) port and platform event filter (PEF) table to generate BMC LAN alerts using the firmware events.
 - `ipmiutil picmg (ipicmg)`—discover the available IPMI LAN nodes on a subnet.
 - `ipmiutil reset (ireset)`—cause the BMC to hard reset or power down the system.
 - `ipmiutil sel (isel)`—a tool to show the firmware system event log (SEL) records.
 - `ipmiutil sensor (isensor)`—show the sensor data records (SDR), readings, and thresholds.
 - `ipmiutil serial (iserial)`—a tool to show and configure the BMC serial port for various modes, for example, Terminal mode.
 - `ipmiutil sol (isol)`—start or stop an IPMI serial-over-LAN console session.
 - `ipmiutil sunoem (isunoem)`—Sun OEM functions.
 - `ipmiutil wdt (iwdt)`—show and set the watchdog timer.
 - `checksel`—cron script using `ipmiutil sel` to check the SEL, write new events to the OS system log, and clear the SEL if nearly full.
 - `ipmi_port`—daemon to bind the remote management control protocol (RMCP) port and sleep to prevent Linux portmap from stealing the RMCP port.
 - `ipmi_wdt`—initial script to restart the watchdog timer every 60 seconds using the cron.
 - `ipmi_asy`—initial script that runs the `ipmiutil getevt -a` command for a remote shutdown.
 - `ipmi_evt`—initial script that runs the `ipmiutil getevt -s` command for monitoring events.
 - `hpiutil/*`—parallel hardware platform interface (HPI) utilities that conform to the SA Forum Hardware Platform Interface. Also a basis of the `openhpi/clients/`
 - `bmc_panic`—a kernel patch to save information if the system panics. The command is found in the OpenIPMI driver in kernels 2.6 and greater and in the Intel IMB driver in version 28 and greater

Dell EMC support

The Dell EMC support site provides documents and tools to help you effectively use Dell EMC equipment and mitigate network outages. Through the support site you can obtain technical information, access software upgrades and patches, download available management software, and manage your open cases. The Dell EMC support site provides integrated, secure access to these services.

To access the Dell EMC support site, go to www.dell.com/support/. To display information in your language, scroll down to the bottom of the web page and select your country from the drop-down menu.

- To obtain product-specific information, enter the 7-character service tag, known as a luggage tag, or 11-digit express service code of your switch and click **Submit**.
- To view the platform service tag or express service code, pull out the luggage tag on the upper-right side of the platform or retrieve it remotely using the `ipmitool -H <bmc ip address> -I lanplus -U <user name> -P <password> fru` command
- To receive more technical support, click **Contact Us**. On the Contact Information web page, click **Technical Support**.

To access switch documentation, go to www.dell.com/manuals/.

To search for drivers and downloads, go to www.dell.com/drivers/.

To participate in Dell EMC community blogs and forums, go to www.dell.com/community.